

STRONG

Mbps
3000
Mbit/s

ATRIA

WI-FI MESH HOME TRIO PACK AX3000

Performant – Reliable - Anywhere

Using state of art Easy Mesh solution, STRONG's Wi-Fi Mesh Home Trio Pack AX3000 combines Mesh technology with the powerful Wi-Fi 6 MU-MIMO standard for ultimate speed and coverage at home.

This package of 3 ATRIA Mesh AX3000 replaces your current Wi-Fi network without changing your modem or router. It brings a super-fast and seamless roaming Wi-Fi network at a speed up to 3000 Mbit/s with coverage up to 525 m².

Depending on the size of your house, you can add up to 3x additional ATRIA Mesh AX3000 (up to 6x ATRIA Mesh AX3000 cover an area of up to 1050 m²).

Manage your Wi-Fi Mesh network at a finger touch with the ATRIA Mesh App available for Android and iOS devices.



Wi-Fi performance



- Supports Wi-Fi 6 (802.11ax/ac/n/g/b/a) standards
- Speed up to 3000 Mbit/s
- Support MU-MIMO and OFDMA technologies
- 574 Mbit/s @2.4GHz + 2402Mbit/s @5GHz
- Support DFS Channels

Coverage & Reliability



- Easy MESH Support for maximum coverage, performance and connectivity
- Up to 254 connected devices capacity
- Multiple Access Points Configuration
- Only one Wi-Fi name all over the house
- Intelligent roaming in Mesh configuration
- Wi-Fi Mesh Trio Pack AX3000 covers up to 525 m²
- Up to 6x ATRIA Mesh AX3000 cover up to 1050 m² on multiple floors

Security



- WPA™/WPA2™ /WPA3™ for Wi-Fi security
- Connect & Secure (WPS) button to add additional ATRIA Mesh AX3000 in few minutes
- Connect & Secure (WPS) button to simply connect your Wi-Fi devices to your Wi-Fi Mesh network

Connections



- 3x Gigabit LAN/WAN Ethernet ports on each ATRIA Mesh AX3000 to connect any computer, set-top-box, Smart TV, NAS, game console, ...
- TR069/TR098/TR181 compliant
- ATRIA Mesh app to manage your Wi-Fi Mesh network at a finger touch
- Mesh/Access Point/ Router operational modes
- Works with any standard modem or router



WI-FI MESH HOME TRIO PACK AX3000

Wi-Fi

Frequency	2412 MHz-2462 MHz & 5180 MHz-5240 MHz & 5250 MHz-5350 MHz & 5470 MHz-5580 MHz
Standard	Wi-Fi 6 - IEEE 802.11ax/ac/n/g/b/a
Signal Rate	5 GHz: Up to 2402 Mbps 2.4 GHz: Up to 574 Mbps
Security	WPA3/WPA2/WPA-PSK/TM & WPA2/TM/WPA-PSK/TM & WPA3-SAE/TM
Antennas	4* Internal Antennas (3dBi)
Transmit Power	Europe: <20 dBm (2.4 GHz), <23 dBm (5 GHz)
Supported Channels	5 GHz: 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112 2.4 GHz: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13

Mesh technology

Easy MESH Compliant	Automatically Organized Network Intelligent Roaming (client band steering) Auto Configuration Seamless Roaming Auto MESH Routing User Load Balancing Auto Healing (Redundancy and Fail-over)
Multiple Access Point architecture Network	Up to 6x ATRIA Mesh AX3000 in one Mesh
Unique Wi-Fi name Ethernet backhaul	Only one Wi-Fi name all over the house Mesh nodes can also be connected through Ethernet for better performances

Hardware

CPU	Dual-core CPU 900MHz
Ethernet Ports	2x 10/100/1000M LAN ports (Auto MDI/MDIX) 1x 10/100/1000M WAN ports (Auto MDI/MDIX)
Buttons	Connect & Secure (WPS), Reset, ON/OFF button
LEDs	Power, Internet, Pairing, 2.4 GHz and 5 GHz Wi-Fi
Power	External power supply, 12V/ 1 A DC
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

Other specifications

Certification	CE
Package Contents	3x ATRIA Mesh AX3000 3x Power Supply Units (12V/ 1 A DC) 1x CAT5E Ethernet Cable 1x Installation Instructions, Warranty Card, Safety
Instructions	
System Requirements	Internet Browser


Software

Multiple SSID	4x2.4 GHz + 4x 5 GHz
Basic Network	DHCP client, IGMP v1/v2, IPv4/v6, WDS, WPS, WMM
Router Features	DHCP server, DNS relay/proxy, NAT/NAPT, IGMP proxy, Firewall, VPN passthrough, DMZ, URL/IP/MAC Filtering, Port Forwarding
UPnP	Universal Plug & Play Internet Gateway Device
Management	TR069/TR098/TR181, Web User Interface, Time Settings, Configuration Backup/Restore, Firmware Upgrade, System Log
ATRIA Mesh app	Android and iOS downloadable app to manage the Wi-Fi Mesh network

Environment

Operating temperature:	0° C ~ +45° C Storage temperature: -20° C ~ +70° C Operating humidity: 10%~90% non-condensing Storage humidity: 10%~90% non-condensing
Dimensions (WxDxH) per unit	128*128*73 mm
Weight per unit	320 g

1. Power LED
2. Pairing LED
3. Internet LED
4. 2.4 GHz LED
5. 5 GHz LED
6. Power supply connector
7. On/Off Power button
8. Reset button
9. Connect & Secure (WPS) button
10. 3x Gigabit LAN/WAN Ethernet ports



EAN MESHTRI1AX3000: 9120072375194
PCB: 6 pcs.

In consequence of continuous research and development technical specifications, design, picture and appearance of products may change without notice. STRONG shall not be responsible in any manner relating to the logos, brands and/or trademarks displayed herein which are not registered by STRONG. All product names are trademarks or registered trademarks of their respective owners. Wi-Fi, WPA3, WPA2, WPA are registered trademarks of Wi-Fi Alliance®. Data throughput, distance, signal range, and coverage area per m² are used only for reference and based on performance test results under normal use case conditions. Actual performances are not guaranteed and may vary due to differences in operating environments, distance and positioning of the products, mix of products used, building materials, wireless and electrical interferences and other adverse conditions.
© STRONG 2023. All rights reserved.