

3.1.2.1	Manufacturer: Wuxi City Xiyou Motor Co., Ltd.		
3.1.2.2	Electronic motor code (as marked on the engine or other means of identification): SEG30C381PA000147		
3.3.3.4	15/30 minutes power: 1.0 kW at 2200 min ⁻¹		
3.1.3.1	Manufacturer: N.A.	N.A.	
3.1.3.2	Application code (as marked on the engine or other means of identification):	N.A.	
3.3.1	Electric vehicle configuration: pure electric/hybrid-electric/mainpower-electric		
3.3.5.2	Category of hybrid electric vehicle: off-vehicle-charging/not-off-vehicle-charging	N.A.	
3.9.2	Maximum assistance factor: N.A.		
Maximum speed			
1.8	Maximum speed of vehicle: 25 km/h (CV*: N.A.)		
3.9.3	Maximum vehicle speed for which the electric motor gives assistance: N.A.		
Drive-train and control			
3.5.3.9	Transmission (type): A		
3.5.4	Gear ratios: 10.37		
3.5.4.1	Final drive ratio: 10.37		
3.5.4.2	Overall gear ratio in highest gear: N.A.		
Installation of tyres			
6.18.1.1	Tyre size designation:	Axle 2: 3.00-10, 42J	
	Axle 1: 3.00-10, 42J		
	Minimum Load capacity index:	Axle 2: 18	
	Axle 1: 16		
	Minimum speed category symbol:	Axle 2: B	
	Axle 1: B		
	Recommended pressure:	Axle 2: 250 kPa	
	Axle 1: 250 kPa		
	Rim size:	Axle 2: 2.5*10	
	Axle 1: 2.5*10		
	Sidecar wheel: N.A.		
Bodywork			
6.20.2.1	Door configuration and number of doors:	N.A.	
6.16.1	Number of seating positions:	1	
6.16.1.1	Location and arrangement:	r1, C1	
Coupling devices			
7.2.8	Type-approval number of coupling-device:	N.A.	
4.0.1	Environmental step: Euro 5 (3/4/5/5*) ⁽¹⁾		
4.0.6	Sound level measured according to: N.A.		
4.0.6.1	Stationary: N.A. dB(A) (CV*: N.A.)		
4.0.6.2	Drive-by: N.A. dB(A) (CV*: N.A.)		
4.0.6.3	Limit value for L _{40m} : N.A. dB(A) (CV*: N.A.)		
3.2.15	Exhaust emissions measured according to: N.A.		
3.2.15.1	Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable:		
	CO:	N.A. mg/km (CV*: N.A.)	
	THC:	N.A. mg/km (CV*: N.A.)	
	NMHC:	N.A. mg/km (CV*: N.A.)	
	NOx:	N.A. mg/km (CV*: N.A.)	
	HC+NOx:	N.A. mg/km (CV*: N.A.)	
	PM:	N.A. mg/km (CV*: N.A.)	
3.2.15.2	Type II test: tailpipe emissions at (increased) idle and free acceleration:		
	HC: N.A. ppm at normal idling speed and: N.A. ppm at high idle speed (CV*: N.A.)		
	CO: N.A. %vol at normal idling speed and: N.A. %vol at high idle speed (CV*: N.A.)		
3.2.15.3	Smoke corrected absorption coefficient: N.A.		
Energy efficiency			
4.0.2	Fuel consumption:	N.A. l or kg/100km (CV*: N.A.)	
4.0.3	CO ₂ emissions:	N.A. g/km (CV*: N.A.)	
4.0.4	Energy consumption:	45 Wh/km (CV*: N.A.)	
4.0.5	Electric range:	50 km (CV*: N.A.)	
Conversion of the performance of the vehicle:			
8.1	Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no		
Additional information:			
9.1	Remarks:	N.A.	
9.2	Exemptions:	N.A.	