

Allround Nitrile Foam PSP 10-510



DESCRIPTION

The PSP Allround Nitrile Foam 10-510 is a glove with a 13 gauge polyester liner covered in a non-ventilated nitrile foam coating on the palm. The back of the glove is open which provides good ventilation and excellent comfort as a result.

The closed nitrile coating provides a good grip on dry, moist and oily environments. The coating is liquid-tight.

Article PSP 10-510 has been tested and certified in accordance with the European Regulation (EU) 2016/425 and the EN-standards EN420 / EN388:2016.

CHARACTERISTICS

- ▲ Polyester liner, 13 gauge
- ▲ Nitrile foam coating
- ▲ Good grip in dry, moist and oily environments.
- ▲ Palm is liquid-tight
- ▲ High wearing comfort
- ▲ Multifunctional
- ▲ Excellent finger dexterity
- ▲ Elasticated knitted cuff
- ▲ Packaged by the dozen (Economy Pack)
- ▲ Various sizes available
- ▲ Certification according to: EN420 / EN388:2016

CERTIFICATIONS





Abrasion resistance = 4 Blade cut resistance = 1 Tear resistance = 2 Puncture resistance = 1 Cut ISO 13997 = X

APPLICATIONS

Construction | Industry | Logistics | Transport | Assembly | Installation | Precision work









PRODUCT INFORMATION

<u> </u>		
Material	Liner: Polyester	
	Coating: Nitrile foam (non-ventilated)	
Color	Grey / Black	
Length (mm)	220-260 Depending on the size	
Cuff	Elasticated knitted cuff	

^{*}Pay attention! Packed in Economy Pack: 12 pairs per bag

ORDER DETAILS

	Size	Item number	Packing Unit	
	07 / S	2.01.10.510.07	12 x 12 (144 pairs)*	
	08 / M	2.01.10.510.08	12 x 12 (144 pairs)*	
	09 / L	2.01.10.510.09	12 x 12 (144 pairs)*	
	10 / XL	2.01.10.510.10	12 x 12 (144 pairs)*	
	11 / XXL	2.01.10.510.11	12 x 12 (144 pairs)*	



^{**} Liquid protection: Note! The degree of protection depends on the coating used.

Cut ISO 13997: The letter A to F indicates the cut resistance according to ISO 13997. X = control not performed or not applicable