



EUROFINS ELECTRICAL TESTING SERVICE (SHENZHEN) CO., LTD.

EMC TEST- REPORT

TEST REPORT NUMBER: EFGX22040293-IE-01-E01



Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China.

Phone: +86-755-82911867
Fax : +86-755-82910749
Page 1 of 43

TABLE OF CONTENTS

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of approval holder	4
1.4	Application details	4
1.5	EUT information	4
1.6	Test standards	4
2	Technical test	5
2.1	Summary of test results	5
2.2	Test environment	5
2.3	Test mode	5
2.4	Test equipment utilized	6
2.5	System Measurement Uncertainty	7
2.6	Test results	8
3	Emission Test	9
3.1	Radiated disturbance	9
3.2	Conducted Emission	14
3.3	Disturbance power	17
3.4	Harmonic current emission	19
3.5	Voltage Changes, Voltage Fluctuations and Flicker	21
4	Immunity Test	23
4.1	Performance Criteria Description in Clause 6 of EN IEC 55014-2	23
4.2	Classification of apparatus	23
4.3	Electrostatic Discharge	24
4.4	Radio frequency electromagnetic fields	26
4.5	Electrical Fast Transients	28
4.6	Surge Immunity	30
4.7	Injected currents(RF continues conducted)	32
4.8	Voltage dips and Interruption	34
5	Test setup Photos	36
6	EUT Photos	39

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter “Description of test item” and are not transferable to any other test items.

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.


The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Electrical Testing Service (Shenzhen) Co., Ltd. available on request or accessible at www.eurofins.com.

Operator:

2022-05-12

Aemon Huang / Project Engineer



Date

Eurofins-Lab.

Name / Title

Signature

Technical responsibility for area of testing:

2022-05-12

Tom Tian / EMC Supervisor

Date

Eurofins

Name / Title

Signature

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

1.2 Testing laboratory

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park, No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Telephone : +86-755-82911867

Fax : +86-755-82910749

1.3 Details of approval holder

Name : NINGBO PRINCE TOYS CO., LTD.
Address : No. 777 East Taoyuan Road, Guanhaiwei Town, Cixi City, Zhejiang, China
Telephone : ./.
Fax : ./.

1.4 Application details

Date of receipt of test item : 2022-04-19
Date of receipt of test sample : 2022-04-19
Date of test : 2022-04-19 to 2022-04-29
Date of issue : 2022-05-12

1.5 EUT information

Product name : children battery ride on motorcycle
Model name : H1
Brand name : ./.
Sample ID : 220419-30-001
Ratings : DC 5V 2A powered by Power supply (Model: HK050V-060050
Input: AC 120-240V, 50/60Hz, 0.2A;
Output: DC 6V 0.5A, 3.0W)
Internal rechargeable battery: DC 6V 4A
Test voltage : AC 120V 50Hz, AC 230V 50Hz for Power supply;
DC 6V by battery.
Additional information : ./.

(General disclaimer:

The above sample(s) and sample information was/were submitted and identified on behalf of the applicant. Eurofins assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information and technical documents.)

1.6 Test standards

Technical standard :

EN IEC 55014-1:2021

EN IEC 55014-2:2021

EN IEC 61000-3-2:2019/A1:2021

EN 61000-3-3:2013/A1:2019

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified were ascertained in the course of the tests performed.



2.2 Test environment

Temperature	:	15	...	35°C
Relative humidity content	:	30	...	60%
Air pressure	:	86	...	106kPa

2.3 Test mode

TM1: Charging (AC 230V 50Hz)
TM2: Charging (AC 120V 50Hz)
TM3: Working (DC 6V)

Only the worst case mode recorded in this report.

2.4 Test equipment utilized

EQUIPMENT ID	EQUIPMENT NAME	MODEL NO.	CAL. DUE DATE
23-2-13-01	EMI Test Receiver	ESR7	2023-03-21
23-2-13-02	Signal Analyzer	N9020B-544	2023-03-21
23-2-12-02	TRILOG Broadband Antenna	VULB9168	2023-04-27
23-2-10-01	Preamplifier	BBV9745	2023-03-21
23-2-13-05	EMI Test Receiver	ESR3	2023-03-21
23-2-13-06	LISN	NNLK 8127 RC	2023-03-21
23-2-10-16	Attenuator	VTSD 9561-F	2023-03-21
23-2-13-16	Harmonic&Flicker test system	100C-CTS-230	2023-03-21
23-2-13-17	Harmonic&Flicker test system	5001iX-CTS-400	2023-03-21
23-2-13-10	ESD Generator	NSG437	2023-03-25
23-2-13-11	Test Generator	compact NX5 bspt-1-300-16	2023-03-21
23-2-13-21	Switch Unit	variac NX-1-260-16	2023-03-21
23-2-13-09	Conducted Immunity Test Set	NSG4070C-35	2023-03-21
23-2-10-31	CDN	CDNM132S	2023-03-21
23-2-10-35	attenuator	DTS60-6dB-1G	2023-03-21
23-2-13-07	Signal Generator	N5171B-506	2023-03-21
23-2-13-08	Power meter	N1914A	2023-03-21
23-2-10-26	Average power sensor	E9301A	2023-03-21
23-2-10-75	Average power sensor	E9301A	2023-03-21
23-2-12-11	Antenna	STLP9129	2023-05-18
23-2-10-69	PC	M4000E-16	N/A
23-2-10-70	LED Monitor	D18215FD0	N/A
23-2-10-71	PC	M4000E-16	N/A
23-2-10-72	LED Monitor	V193HQV	N/A
23-2-10-73	PC	T4099V-00	N/A
23-2-10-74	LED Monitor	LS2224	N/A
23-2-18-001	Test software	CTS 4	N/A
23-2-18-002	Test software	NSG 4070 control program	N/A
23-2-18-003	Test software	iec.control	N/A
23-2-18-005	Test software	TS+VER2.1-JS32-CE	N/A
23-2-18-006	Test software	TS+VER2.1-JS35-RS	N/A
23-2-18-007	Test software	TS+VER2.1-JS32-RE	N/A

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

2.5 System Measurement Uncertainty

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.56dB; Vertical: 4.55dB;
Uncertainty for Conducted Emission 150kHz-30MHz	1.96dB
Uncertainty for Flicker test	3.76%
Uncertainty for CS test	28%(CDN), 45%(EM Clamp) K=2
Uncertainty for RS test	25%, K=2
Uncertainty for ESD test	The immunity measurement system uncertainty is within standard requirement and is based on a standard uncertainty multiplied by a coverage factor k=2, providing a level of confidence of approximately 95%.
Uncertainty for EFT test	
Uncertainty for Surges test	
Uncertainty for Voltage Dips, Voltage Variations and Short Interruptions Test	

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

2.6 Test results

 1st test

 test after modification

 production test

Test item	Sub clause	Required	Test passed	Test failed
Conducted Emission	Clause 4.3.2 & 4.3.3 of EN IEC 55014-1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Disturbance power	Clause 4.3.4.4 of EN IEC 55014-1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated disturbance (30MHz to 1000MHz)	Clause 4.3.4 of EN IEC 55014-1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated disturbance (1000MHz to 6000MHz)	Clause 4.3.5 of EN IEC 55014-1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Magnetic field (equipment using IPT)	Clause 4.3.2 of EN IEC 55014-1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Discontinuous disturbance	Clause 4.4.2 of EN IEC 55014-1	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Harmonic Current Emissions	EN IEC 61000-3-2	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Voltage Changes, Voltage Fluctuations and Flicker	EN 61000-3-3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Electrostatic Discharge	Clause 5.1 of EN IEC 55014-2 & IEC 61000-4-2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Electrical Fast Transients	Clause 5.2 of EN IEC 55014-2 & IEC 61000-4-4	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Injected currents (RF continues conducted)	Clause 5.3 & 5.4 of EN IEC 55014-2 & IEC 61000-4-6	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radio frequency electromagnetic fields	Clause 5.5 of EN IEC 55014-2 & IEC 61000-4-3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surge immunity	Clause 5.6 of EN IEC 55014-2 & IEC 61000-4-5	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Voltage dips and Interruption	Clause 5.7 of EN IEC 55014-2 & IEC 61000-4-11	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Note:

- The click rate was less than 5, and the click duration was less than 10ms. So it is deemed to comply with Discontinuous disturbance test.
- The Harmonics current emission test was not required as the rated power of EUT was less than 75W.

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

3 Emission Test

3.1 Radiated disturbance

This clause lays down the general requirements for the measurement of Radiated disturbance produced at the space of apparatus.

3.1.1 Limits

Frequency range MHz	Peak limits at 3m dB (μ V/m)	Quasi-peak limits at 3m dB (μ V/m)	Average limits at 3m dB (μ V/m)
30 to 230	/	40	/
230 to 1000	/	47	/
1000 to 3000	70	/	50
3000 to 6000	74	/	54

At transitional frequencies the lower limit applies.


Note 1: Result Level= Read Level + Corrector Factor

Note 2: Below 1GHz: Corrector factor = Antenna Factor + Cable Loss - Amplifier Gain.

Note 3: Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain.

Note 4: Radiated disturbance test in the frequency range from 1 GHz to 6 GHz is not required as the highest clock frequency (Fx) of EUT is less than 108MHz.

3.1.2 Measurement procedure



1. The radiated emissions test was conducted in a semi-anechoic chamber. The EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was

placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.


2. Before get the final emission results with quasi-peak(QP) detector, a pre-scan was performed with the peak(PK) detector to find out the maximum emission data plots of the EUT.

3. The frequencies of maximum emission were determined in the final radiated emissions measurement, the physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization. Test was performed at 3 m distance.

3.1.3 Test environment

Temperature : 24.6 °C
 Relative humidity content : 57.6 %
 Air pressure : 101.5 kPa


3.1.4 Results



Final Data List								
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	41.1606	-15.76	37.24	40.00	2.76	100	294	Vertical
2	69.7899	-18.39	19.22	40.00	20.78	100	347	Vertical
3	103.7569	-19.95	27.38	40.00	12.62	100	269	Vertical
4	158.1041	-15.77	17.45	40.00	22.55	100	347	Vertical
5	198.8644	-18.98	23.96	40.00	16.04	100	347	Vertical
6	229.4347	-18.45	20.03	40.00	19.97	100	287	Vertical

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China


Horizontal Polarity Test Data


Final Data List								
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	41.6458	-15.76	21.65	40.00	18.35	100	359	Horizontal
2	88.2291	-21.37	14.01	40.00	25.99	100	112	Horizontal
3	107.1536	-19.67	22.11	40.00	17.89	100	192	Horizontal
4	138.6943	-16.34	20.27	40.00	19.73	100	112	Horizontal
5	194.9825	-18.65	26.15	40.00	13.85	100	360	Horizontal
6	227.4937	-18.61	26.12	40.00	13.88	100	360	Horizontal

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China


TM3
Vertical Polarity Test Data



Final Data List								
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	81.9210	-20.89	18.36	40.00	21.64	100	275	Vertical
2	124.6223	-18.06	21.57	40.00	18.43	100	296	Vertical
3	162.9565	-15.96	16.88	40.00	23.12	100	258	Vertical
4	200.8054	-19.08	16.50	40.00	23.50	100	292	Vertical
5	444.8824	-12.93	20.40	47.00	26.60	100	266	Vertical
6	928.1841	-5.40	33.02	47.00	13.98	100	334	Vertical

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Horizontal Polarity Test Data


Final Data List								
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	102.7864	-20.03	24.08	40.00	15.92	100	292	Horizontal
2	167.8089	-16.34	22.86	40.00	17.14	100	347	Horizontal
3	205.1726	-19.12	24.68	40.00	15.32	100	147	Horizontal
4	325.9980	-15.19	25.39	47.00	21.61	100	347	Horizontal
5	514.2721	-11.46	31.80	47.00	15.20	100	193	Horizontal
6	903.4367	-5.84	37.28	47.00	9.72	100	345	Horizontal

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

3.2 Conducted Emission


This clause lays down the general requirements for the measurement of disturbance voltage produced at the terminals of apparatus.

3.2.1 Limits

Frequency range MHz	At mains terminals dB (μ V)	
	Quasi-peak Limit	Average Limit
0.15 to 0.50	66 to 56	59 to 46
0.50 to 5	56	46
5 to 30	60	50

Note1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 30 MHz.
 Note2: The lower limit is applicable at the transition frequency.

3.2.2 Measurement procedure



1. The mains terminal disturbance voltage was measured with the EUT in a shielded room.
2. The EUT was connected to AC power source through a LISN (Line Impedance Stabilization Network) which provides a $(50 \mu\text{H} + 5 \Omega) \parallel 50 \Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN, which was bonded to the ground reference plane in the same way as the LISN for the unit being measured.
3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
4. Before get the final emission results with quasi-peak(QP) detector and average(AV) detector, a pre-scan was performed with the peak(PK) and average(AV) detector to find out the maximum emission data plots of the EUT.


Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China


3.2.3 Test environment

Temperature : 25.1 °C
 Relative humidity content : 57.3 %
 Air pressure : 101.5 kPa

3.2.4 Results -Measurement Data



Final Data List										
NO.	Freq. [MHz]	Factor [dB]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Type	Verdict
1	0.4151	10.25	23.32	57.55	34.23	14.43	48.01	33.58	L	PASS
2	0.5272	10.27	35.84	56.00	20.16	30.32	46.00	15.68	L	PASS
3	0.7945	10.28	27.83	56.00	28.17	16.69	46.00	29.31	L	PASS
4	1.3216	10.31	26.46	56.00	29.54	15.28	46.00	30.72	L	PASS
5	1.8943	10.35	30.31	56.00	25.69	19.13	46.00	26.87	L	PASS
6	3.0291	10.37	25.26	56.00	30.74	16.53	46.00	29.47	L	PASS

Neutral line test data

Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Type	Verdict
1	0.5293	10.27	41.68	56.00	14.32	33.72	46.00	12.28	N	PASS
2	1.1821	10.28	35.23	56.00	20.77	25.61	46.00	20.39	N	PASS
3	1.7533	10.30	36.32	56.00	19.68	26.01	46.00	19.99	N	PASS
4	2.4555	10.30	35.32	56.00	20.68	24.98	46.00	21.02	N	PASS
5	3.2210	10.32	35.60	56.00	20.40	25.04	46.00	20.96	N	PASS
6	9.1822	10.45	37.10	60.00	22.90	24.16	50.00	25.84	N	PASS

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
 1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
 No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

3.3 Disturbance power

This clause lays down the general requirements for the measurement of disturbance power produced at the terminals of apparatus.

3.3.1 limits

Table 2a-Disturbance power limits for the frequency range 30 MHz to 300 MHz


Frequency range MHz	Limit dB (pW)	
	Quasi-peak	Average
30 to 300	45 to 55	35 to 45

Note: Increasing linearly with the frequency from.
If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out.

Table 2b-Margin when performing disturbance power measurement in the frequency range 30 MHz to 300 MHz

1	Household and similar appliances		Tools					
	2	3	4	5	6	7	8	9
Frequency range			Rated motor power not exceeding 700 W		Rated motor power above 700 W and not exceeding 1 000 W		Rated motor power above 1 000 W	
(MHz)	dB (pW) Quasi-peak	dB (pW) Average	dB (pW) Quasi-peak	dB (pW) Average	dB (pW) Quasi-peak	dB (pW) Average	dB (pW) Quasi-peak	dB (pW) Average
Increasing linearly with the frequency from:								
200 to 300	0 to 10 dB	-	0 to 10 dB	-	0 to 10 dB	-	0 to 10 dB	-

3.3.2 Measurement procedure



Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

The test configuration corresponds to the standard EN IEC 55014-1. The equipment under test is placed on a non metallic table with 0,8 m high. The lead to be measured is stretched horizontally in a straight line, to permit variation in position of the absorbing clamp along the lead to find the maximum indication. The lead shall be at least length of 6 meter. Before get the final emission results with quasi-peak(QP) detector and average(AV) detector, a pre-scan was performed with the peak(PK) detector to find out the maximum emission data plots of the EUT. The absorbing clamp is placed around the lead.

3.3.3 Test environment

Temperature	: °C
Relative humidity content	: %
Air pressure	: kPa

3.3.4 Results

N/A

3.4 Harmonic current emission


This part deals with the limitation of harmonic currents injected into the public supply system.

3.4.1 Limits

Limit for Class A equipment

Harmonic order n	Maximum permissible harmonic current A
Odd harmonics	
3	2,30
5	1,14
7	0,77
9	0,40
11	0,33
13	0,21
$15 \leq n \leq 39$	$0,15 \frac{15}{n}$
Even harmonics	
2	1,08
4	0,43
6	0,30
$8 \leq n \leq 40$	$0,23 \frac{8}{n}$

3.4.2 Measurement procedure



The equipment under test is placed on a wooden table with a height of 0,8 m in the EMC lab. For each harmonic order, measure the 1,5 s smoothed r.m.s. harmonic current in each DFT time window and calculate the arithmetic average of the measured values from the DFT time windows, over the entire observation period. Each harmonic order, all 1.5 s smoothed r.m.s. harmonic current values and the average values for the individual harmonic currents, taken over the entire test observation period shall be less than or equal to the applicable limits.

3.4.3 Test environment

Temperature : °C
Relative humidity content : %
Air pressure : kPa

3.4.4 Results

N/A


3.5 Voltage Changes, Voltage Fluctuations and Flicker

This part is concerned with the limitation of voltage fluctuations and flicker impressed on the public low-voltage system.

3.5.1 Limits

Value	Limit
Pst	1,0
Plt	0,65
dt	3,3%
dc	3,3%
dmax	4,0%

3.5.2 Measurement test procedure



The equipment under test is placed on a wooden table with a height of 0,8 m in the EMC lab. The voltage fluctuations and flicker were measured at the supply terminals of the EUT.

3.5.3 Test environment

Temperature : 24.2 °C
 Relative humidity content : 56.2 %
 Air pressure : 101.5 kPa

3.5.4 Results

TM1

Parameter values recorded during the test:

Vrms at the end of test (Volt):	229.51			
T-max (mS):	0	Test limit (mS):	500.0	Pass
Highest dc (%):	0.00	Test limit (%):	3.30	Pass
Highest dmax (%):	0.00	Test limit (%):	4.00	Pass
Highest Pst (10 min. period):	0.200	Test limit:	1.000	Pass

4 Immunity Test

4.1 Performance Criteria Description in Clause 6 of EN IEC 55014-2

Criterion A:	The apparatus shall continue to operate as intended during the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.
Criterion B:	The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. During the test, degradation of performance is allowed, however. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation and from what the user may reasonably expect from the apparatus if used as intended.
Criterion C:	Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls, or by any operation specified in the instructions for use.


4.2 Classification of apparatus

Category I:	Apparatus containing no electronic control circuitry.
Category II:	Mains operated equipment containing electronic control circuitry with no clock frequency higher than 15 MHz.
Category III:	Battery operated equipment not included in Category I.
Category IV:	Mains operated equipment containing electronic control circuitry with a highest clock frequency greater than 15 MHz but lower than or equal to 200 MHz.
Category V:	Mains operated equipment containing electronic control circuitry with a highest clock frequency greater than 200 MHz.

The EUT belongs to Category III + Category II (while connected to AC mains).

4.3 Electrostatic Discharge

4.3.1 Test Procedures



1. Contact discharge was applied only to conductive surfaces of the EUT. Air discharge was applied only to non-conducted surfaces of the EUT.
2. The EUT was put on a 0.8m high wooden table for table-top equipment or 0.1m high for floor standing equipment standing on the ground reference plane (GRP).
3. A horizontal coupling plane(HCP) 1.6m by 0.8m in size was placed on the table, and the EUT with its cables were isolated from the HCP by an insulating support thick than 0.5mm. The VCP 0.5m by 0.5m in size while HCP were constructed from the same material type and thickness as that of the GRP, and connected to the GRP via a 470kΩ resistor at each end. The distance between EUT and any of the other metallic surfaces excepted the GRP, HCP and VCP was greater than 1m.
4. During the contact discharges, the tip of the discharge electrode was touching the EUT before the discharge switch is operated. During the air discharges, the round discharge tip of the discharge electrode was approached as fast as possible to touch the EUT. After each discharge, the ESD generator was removed from the EUT, the generator is then retriggered for a new single discharge. For ungrounded product, a discharge cable with two resistances was used after each discharge to remove remnant electrostatic voltage. 10 times of each polarity single discharge were applied to HCP and VCP.

4.3.2 Test environment

Temperature : 24.1 °C
 Relative humidity content : 56.2 %
 Air pressure : 101.5 kPa


4.3.3 Results

TM1						
Test point	Table (T) Floor (F)	Contact (C) Air (A)	Voltage (Kv)	Number of discharge	Polarity (+ / -)	Opinion
Air discharge	T	A	±2, ±4, ±8	Mini 20/point	+ / -	A
Direct discharge	T	C	±2, ±4	Mini 20/point	+ / -	A
HCP	T	C	±2, ±4	Mini 20/point	+ / -	A
VCP	T	C	±2, ±4	Mini 20/point	+ / -	A

A: no loss of function.
 N/A: Not Applicable.

4.4 Radio frequency electromagnetic fields

4.4.1 Measurement procedure



1. The EUT was placed on 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP. The tests normally shall be performed with the generating antenna facing each of four sides of the EUT. When equipment can be used in different orientations (e.g. vertical or horizontal) the test shall be performed on all possible sides of the EUT.
2. The tests are carried out with a field strength by 3 V/m (measured in the unmodulated field) with amplitude modulated signal by a depth of 80 % by a sinusoidal audio signal of 1 kHz. The logarithmic step was 1% and the dwell time was 3s dependent of the EUT cycle time.

4.4.2 Test environment

Temperature : 24.2 °C
 Relative humidity content : 56.2 %
 Air pressure : 101.5 kPa

4.4.3 Results


TM3

Frequency Range	Field Strength	Modulation	Antenna Polarity	Opinion
80MHz-1GHz	3V/m	80% AM 1kHz	Horizontal	A
80MHz-1GHz	3V/m	80% AM 1kHz	Vertical	A

A: no loss of function.

4.5 Electrical Fast Transients

4.5.1 Measurement procedure



1. The EUT was placed on a ground reference plane (GRP) insulated by an insulating support 0.1 m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
2. The GRP shall project beyond the EUT and the clamp by at least 0.1m on all sides. The distance between the EUT and any other of the metallic surface except the GRP was greater than 0.5m. All cables to the EUT was placed on the insulation support 0.1m above GRP. Cables not subject to EUT was routed as far as possible from cable under test to minimize the coupling between the cables.
3. The length of signal and power cable between the EUT and EFT generator was 0.5m. If the cable is a non-detachable supply cable more than 0.5m, the excess length of this cable shall be folded to avoid a flat coil and situated at a distance of 0.1m above the GRP.

4.5.2 Test environment

Temperature : 24.2 °C
 Relative humidity content : 56.3 %
 Air pressure : 101.5 kPa

4.5.3 Results

TM1

Test port	Voltage (kV)	Polarity (+ / -)	Duration (s or min)	Waveform Tr / Th	Repetition Frequency (kHz)	Opinion
a.c. port, L	1	+/-	2 min	5/50 ns	5	A
a.c. port, N	1	+/-	2 min	5/50 ns	5	A
a.c. port, PE	1	+/-	2 min	5/50 ns	5	N/A
a.c. port, L+N	1	+/-	2 min	5/50 ns	5	A
a.c. port, L+PE	1	+/-	2 min	5/50 ns	5	N/A
a.c. port, N+PE	1	+/-	2 min	5/50 ns	5	N/A
a.c. port, L+N+PE	1	+/-	2 min	5/50 ns	5	N/A


A: no loss of function.

B: the appliance could not work normal during test, but after test it would recover automatically.

N/A: Not Applicable.

4.6 Surge Immunity

4.6.1 Measurement procedure



1. The EUT was placed on a ground reference plane (GRP) insulated by an insulating support 0,1 m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
2. The 1,2/50 μ s surge was to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks were required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines and to provide sufficient decoupling impedance to the surge wave so that the specified wave may be applied on the lines under test.
3. The positive pulses are applied 90° relative to the phase angle of the a.c. line voltage to the equipment under test, and the negative pulses are applied 270° relative to the phase angle of the a.c. line voltage to the equipment under test.

4.6.2 Test environment

Temperature : 24.2 °C
 Relative humidity content : 56.3 %
 Air pressure : 101.5 kPa

4.6.3 Results


TM1

Test port	Polarity (+ / -)	Voltage (kV)	Voltage Waveform	Current Waveform	Repetition Rate	Number of pulses	Opinion
a.c. port, L-N	+/-	1.0	1.2/50 μs	8/20 μs	1 per min	5 /point	A
a.c. port, L-PE	+/-	2.0	1.2/50 μs	8/20 μs	1 per min	5 /point	N/A
a.c. port, N-PE	+/-	2.0	1.2/50 μs	8/20 μs	1 per min	5 /point	N/A

A: no loss of function.
 N/A: Not Applicable.

4.7 Injected currents(RF continues conducted)

4.7.1 Measurement procedure



1. The EUT was placed on an insulating support of 0.1m height above a ground reference Plane, arranged and connected to satisfy its functional requirement. All cables exiting the EUT was supported at a height of at least 30 mm above the ground reference plane.
2. The coupling and decoupling devices were required, they were located between 0,1 m and 0,3 m from the EUT. This distance was to be measured horizontally from the projection of the EUT on to the ground reference plane to the coupling and decoupling device.
3. The frequency range was swept from 150 kHz to 80 MHz, using the signal levels established during the setting process, and with the disturbance signal 80 % amplitude modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or to change coupling devices as necessary. Where the frequency was swept incrementally, the step size do not exceed 1 % of the preceding frequency value. The dwell time of the amplitude modulated carrier at each frequency was not less than the time necessary for the EUT to be exercised and to respond, and was not less than 3s.

4.7.2 Test environment

Temperature : 24.1 °C
Relative humidity content : 56.2 %
Air pressure : 101.5 kPa

4.7.3 Results


TM1

Test port	Voltage (e.m.f.)	Modulation	Frequency Range	Opinion
AC power line	3V	80% AM1 kHz	150 kHz - 80 MHz	A

A: no loss of function.
N/A: Not Applicable.

4.8 Voltage dips and Interruption

4.8.1 Measurement procedure



1. The EUT was placed on a ground reference plane (GRP) insulated by an insulating support 0,1 m thick and the GRP was placed on a 0.8m high wooden table for table-top equipment. For floor standing equipment, the EUT was placed on a 0.1m high wooden support above the GRP.
2. The test was performed with the EUT connected to the test generator with the shortest power supply cable as specified by the EUT manufacturer. Voltage change shall occur at zero crossing.
3. The EUT was tested for each selected combination of test level and duration with a sequence of three dips /interruptions with intervals of 10 s minimum. Each representative mode of operation was tested.

4.8.2 Test environment

Temperature : 24.1 °C
 Relative humidity content : 56.2 %
 Air pressure : 101.5 kPa

4.8.3 Results

TM1

Reduction of supply voltage	Test level in % U_T	Duration in parts of period (in ms)	Opinion
100%	0	0.5 (10 ms)	B
60 %	40	10 (200 ms)	B
30 %	70	25 (500 ms)	B


A: no loss of function.

B: the appliance could not work normal during test, but after test it would recover automatically.


N/A: Not Applicable.

5 Test setup Photos

Conducted Emission Test setup



Radiated disturbance Test setup




Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Voltage Fluctuations and Flicker Test setup



Electrostatic Discharge Test setup




Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Hugu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China

Electrical Fast Transients Immunity/ Surge Immunity/ Voltage DIPS
and Interruption Test setup



Injected Currents (RF common mode) Test setup



Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Hugu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China





Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Hugu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China



Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huihu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China



Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China



---End of Report---

Test Report No.: EFGX22040293-IE-01-E01

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.
1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park,
No. 83 Dabao Road, Bao'an District, Shenzhen, P. R. China