

ILCANDE27DC042



Integral Filament Omni Lamps utilise Filament LED technology and a full-glass body to create a decorative look and wide beam angle that looks fantastic in chandeliers and fittings where the lamp is exposed. These retrofit lamps are highly efficient and are an ideal replacement for traditional tungsten filament bulbs.

Details

Barcode: 5055788221890 Category: Lamps Range Name: Omni Product Type: Candle Market Segment: Commercial indoor, Residential indoor Warranty (Years): 2 CE RoHS: Yes

Physical Data

Product Length (mm): 92 Product Width (mm): 35 Product Weight (g): 19 Material: Glass Base Term: Edison screw Bulb Base: E27 Construction: Glass shell, filament strip Globe Finish: Clear Globe Type: Candle Bulb Fixing: Pendant, Wall, lamp stand, table lamp Bulb or Luminaire Shape: Oval Placement / Application: Indoor, General Lighting

Electrical Data

Power (W): 4.5 Power Consumption (w): 4.5 Power Consumption (Range): 3 to 5 Power Factor: 0.7 Voltage Range (v): 220-240 Wattage equivalent (W): 40 Amperage (mA): 27 Dimming: Dimmable Driver Included: Yes Electric Current: AC EN: EN-62560 LVD Certified: Yes

Light Data

Luminous Flux in Lumens (Im): 470 Luminous efficacy (Im/W): 104 Correlated Colour Temperature (CCT) (K): 2700 Colour Temperature: 2700K - Warm Colour Temperature Name: Warm Beam Angle: 300, 330 Colour Rendering Index (CRI): 80 Compatible Dimmers: Varilight JQP401W Frequency Range (Hz): 50 Instant on (Less than 1 second): Yes LED Type: Filament chip Lifetime (hours): 15000 Switching Cycles: 7500

Environment

EN: EN-62560 LVD Certified: Yes CE RoHS: Yes **Energy Rating:** A++ Hg 0% (Mercury Free): Yes IP Rating (Ingress Protection): IP20 Lowest Operating Temperature (°C): -20 Maximum Operating Temperature (°C): 45



Packaging

Package Weight (g): 69 Package Length (mm): 108 Product Design And Specification Subject To Change Or Modification Without Notice. Image For Illustration Only. E&OE

Portal.integral-led.com

Package Width (mm): 42 Package Depth (mm): 42 Qty per euro pallet: 2400

Portal.integral-led.com