

INSTALLATION GUIDELINE

<p>1 Cut bolts if needed. File bolt ends.</p>	<p>2 Mount the sleeve on the bolts and remove inlet plug.</p>	<p>3 Slide on the gaskets on the inlet & outlet pipe as shown.</p>	<p>4 Install the accessory kit into the installation hole of the toilet. (If not assembled)</p>
<p>5 Slide the inlet pipe into the wall openings for waste pipe. Test fit the toilet.</p>	<p>6 Note the distance between the wall and the toilet at the location shown. Measure excess length "A" for the inlet pipe.</p>	<p>7 Remove the toilet. Cut and file the inlet pipe to the proper length by removing excess length "A"</p>	<p>8 Slide the outlet pipe into the wall openings for waste pipe. Test fit the toilet.</p>
<p>9 Note the distance between the wall and the toilet at the location shown. Measure excess length "B" for the outlet pipe.</p>	<p>10 Remove the toilet. Cut and file the outlet pipe to the proper length by removing excess length "B"</p>	<p>11 Add silicon sealant in the gasket grooves.</p>	<p>12 Mount the toilet on the wall.</p>
<p>13 Level the toilet and tighten accessories using allen key or tool provided.</p>	<p>14 Flush the toilet. Check for leaks. Seal connections if required.</p>	<p>15 Seal around the edges. Do not use cement.</p>	

Recommended Installation Parts

<p>Inlet Connection (Not Supplied)</p>		<p>Wall Installation Kit** 1279117</p>	<p>OR</p> <p>Wall Installation Kit** RTA097NF</p>
<p>Outlet Connection (Not Supplied)</p>			

Note:- Dimension A and B (as shown in picture 6 to 10 above) to be adjusted as per specific site requirements.
 **Wall Installation kit shown is supplied with toilet.