

# EU Type Examination Certificate

Date: 2019/01/30

n. **158190521/OE**

Validity:  
2024/01/29

This Certificate cancels & replaces the previous one n° 158173502/OE dated 2017/09/01

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	<b>GRISPORT SpA calzaturificio</b> 31030 CASTELCUCCO (TV) – Via Erega, 1 – ITALIA	
Type of PPE:	<b>Safety footwear</b> in conformity with <b>EN ISO 20345:2011 class I</b> (= footwear in leather and other materials)	
Category of PPE:	<b>II</b> : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.	
Model	<b>"0033260 - 72401"</b>	
Description:	 <p><u>design</u>: C (half-knee boot); <u>fastening system</u>: none (tubular model); <u>process</u>: direct injection; <u>outsole</u>: black rubber marked "SAFETY VERA GOMMA HRO OIL RESISTANT ANTISTATIC MADE IN ITALY ABS ANTISHOCK" (cod. 2137BCP/00 022/ 1/00); <u>midsole</u>: coffee-coloured PU foam (cod. MPI/001); <u>scuff-resistant covering of the toe region</u>: same material as that of the midsole; <u>upper</u>: black leather DAKAR TREKKING IDRO (declared thickness 2,0/2,2 mm - cod. DAI/NER) with a reinforcement SUPPORT SYSTEM (cod. G001NG) made of black polymeric material in the heel area; <u>heel-grip</u>: grey fabric SPOTEX TEPOR SELENE (cod. SPO/SELG), which also covers the insole; <u>front/rear lining</u>: beige coloured lining made of wool + lining Tepor to be heat-sealed (cod. LST/BEI); <u>insole</u>: white multilayer fabric ZP01/1500 (cod. LC/ZP01), covered by the lining and <u>which also serves as penetration resistant insert</u>; <u>removable insock</u>: black foam material with a silver coloured lower surface matched with green non-woven fabric in contact with the foot and an oval insert made of aluminium stitched with antistatic thread to the underside of the foot (cod. FLV+CAA); <u>toecap</u>: perforated and reinforced steel article 604FR (cod. 604ACRF).</p>	
Technical Standard:	<b>EN ISO 20344:2011</b> (UNI EN ISO 20344:2012)	Personal protective equipment – Test methods for footwear
	<b>EN ISO 20345:2011</b> (UNI EN ISO 20345:2012)	Personal protective equipment – Safety footwear
Intended use:	general industry, engineering industry, agriculture, warehouses.	
Size range:	from 39 to 47	
Technical File:	<b>DC-9526/E + DC-8322/E</b>	
Test report:	<b>RCT n°363002</b>	



