




## PUMP UP YOUR BOARD:



The pin must be UP before pumping! If it's down: press the pin down and turn it "counter clockwise" until the pin pops up.



Turn the tube on the pump at the "inflate" input. Put the nozzle into the air valve and turn it "clockwise"



Start pumping in Double Action (with the red nipple in the pump) to about 0,3 BAR (7 PSI). Then switch to Single Action (turn the red nipple off) and fill to maximum 1,0 bar (15PSI). This is a good warming up...!



Always lock the valve cover when in use. Keep it free of sand and rinse the valve part in fresh water after use



## BOARD DEFLATION:

Deflate by pressing the pin down. Fixate the pin by turning it "clockwise". Don't mind the air that escapes!

**BEWARE:** Place your board in the shadow if you're not on the water and reduce pressure to prevent overpressure and damage of your SUP board! Especially in sunny and warm conditions!

## FIN PLACEMENT:



After the board is pumped up, slide in the Fin and insert the fixing stick. Always turn the SUP upside down on the waterfront, so that it does not lean on the fin.

## LEASH:



You can mount the leash yourself at the desired position on the board: on one of the deck rings or the central position on the center handle.




## **STORAGE:**

Roll up the SUP from the front to the back. So roll over to the valve and make sure it's open. Do not roll up the SUP too tightly to avoid sharp folds in the PVC. This is how the SUP fits perfectly in the backpack.

## **MAINTENANCE:**

- Place your SUP in the shadow when not in use. When the weather is hot (>25 degrees), we suggest to pump until 12 PSI.
- Before storing, deflate the board and let it dry completely to prevent mildew.
- We suggest storage indoor and between +10 and 30 degrees
- Losing air in the vent? Use the tool (Valve handle) to fix the valve tight (in the repair set):
  1. Press the pin to deflate the SUP
  2. With one hand press the valve handle in the vent and turn the handle clockwise carefully. It is normal to do it ones a year, because it comes loose from usage.
  3. Attention: The valve handle is for repair only, DO NOT use it for normal inflate or deflate!



## **PADDLE:**

Slide the loose paddle together. To get the right paddle length, you can adjust the top of the paddle by sliding the lock backwards with two fingers at the same time. Then move it to the correct length and secure it again. The ideal paddle length is 20 centimeters above your head.

