

# SEVERIN



2 YEAR WARRANTY



TO 2052



9 L 800 W



# SEVERIN



## Toast oven

Horno tostador  
Forno  
Minipekarnik

9 L 800 W



# SEVERIN

**DE** Hochhitzebeständige Lackierung, Außenmaße ca. L = 358, T = 310, H = 210 mm  
**GB** Highly heat-resistant painting, exterior dimensions: (W) 358, (D) 310, (H) 210 mm  
**FR** Finition laque thermorésistante, dimensions extérieures: L = 358, P = 310, H = 210 mm  
**NL** Hoge hittebestendige verfassing, afmetingen: L = 358, D = 310, H = 210 mm  
**DK** Høje hittebestandigt lakering, mål: L = 358 mm, D = 310 mm, H = 210 mm  
**ES** Recubrimiento de pintura resistente al calor, dim. exteriores: ancho 358 mm, profundo 310 mm, alto 210 mm  
**IT** Verniciatura di rivestimento altamente resistente al calore, dimensioni: L = 358 mm, P = 310 mm, A = 210 mm  
**PL** Okładzina polistyru bardzo odporna na wysokie temp., wymiary gabarytowe Dł = 358 x Gł = 310 x Wys = 210 mm

**DE** Mit Backblech und Grill, Geräum ca. 9 l, ca. 800 W  
**GB** With baking tray and grill rack, 9 l interior capacity, approx. 800 W  
**FR** Avec plat de cuisson et grille, capacité 9 l, env. 800 W  
**NL** Met bakplaat en rooster, inhoud ca. 9 l, ongeveer 800 W  
**DK** Med bageplade og rist, rumrum 9 liter, ca. 800 W  
**ES** Con bandeja de cocinado y rejilla, capacidad 9 l, aprox. 800 W  
**IT** Con griglia e tegame da forno. Capacità ca. 9 litri, ca. 800 W  
**PL** Kształki grillowa oraz forma do pieczenia, pojemność 9 l, ok. 800 W

[www.severin.de](http://www.severin.de)



# SEVERIN



## Toastofen

Tostovn  
Mini four réchauffeur  
Toast oven

9 L 800 W



# SEVERIN

**DE** 4-Stufen-Schalter: Aus - Oberhitze - Unterhitze - Ober- und Unterhitze, Kontrollleuchte  
**GB** 4 stage switch: off - top heat - bottom heat - top and bottom heat, pilot light  
**FR** Interrupteur à 4 positions: arrêt - résistance de voile - résistance de sole - résistances de voile et de sole, voyant lumineux  
**NL** 4 standen schakelaar: uit - bovenverwarming - onderverwarming - order en bovenverwarming, controlelampje  
**DK** 4-tæts skiftelær: ude - overvarme - undervarme - over og undervarme, kontrollys  
**ES** Interruptor de 4 posiciones: apagado - elemento superior - elemento inferior - elementos superior e inferior, luz piloto  
**IT** Interruttore a 4 posizioni: spento - riscaldamento dall'alto - riscaldamento dal basso - riscaldamento dall'alto e dal basso, spia di controllo  
**PL** 4 stopniowy przełącznik: wyłączony - górne grzanie - dolne grzanie - górne i dolne grzanie, lampka kontrolna

**DE** 60 min. Timer mit Signalton nach Beenden der vorgeählten Zeit  
**GB** 60 minute timer with bell  
**FR** Minuteur sonore 60 minutes  
**NL** 60 min. timer met signaltone na beëindiging baktijd  
**DK** 60 min. timer med signaltone efter indstillet tid  
**ES** Temporizador de 60 minutos con timbre  
**IT** Timer da 60 minuti con segnale acustico finale  
**PL** 60 minutowy zegar z sygnałem dźwiękowym o zakończeniu procesu

[www.severin.de](http://www.severin.de)

CE

220 - 240 V ~

800 W



TO 2052

SEVERIN Elektrogeräte GmbH  
Röhre 27  
60846 Sundern  
Germany  
www.severin.de

Manufactured in China - according to German quality standards

