

ring lamp bracket



Specitfications:

Model	ring lamp bracket
Parameters	
Material	ABS/PC/Metal rod
power	10W
Charging	USB
LED Light beads	108pcs
Brightness level	10
Product size	10"

How to Choose Lighting Mode



USB Cable Powered



Installation method:



1.Remove the tripod, pull the top bracket up,select the appropriate height and tighten and secure nut ①

2. Screw the ④ hose mobile phone clamp to the ③ hose hole,then screw the ⑤ camera head screw to the ③ threaded hole, and then screw the ⑥ tripod to the ⑤ threaded hole. After all the accessories are installed,the mobile phone can be used





90°

180°



The universal joint has a spherical design and can be rotated 360 degrees for easy use at any angle.

360° rotation



Pan tilt can rotate 360 °

Use size: 5-8.5cm
Basically compatible with all types of mobile phones on the market



Product accessories:



How to connect Bluetooth remote with cellphone?



1. Turn on the Bluetooth remote control button, and the blue light flashes to indicate that you have entered the pending wireless connection.
2. Wireless Bluetooth search from the mobile phone, find the Bluetooth name 'AB SHUTTER3.0', wait until the blue light goes out. indicating that the link has been successful with the mobile phone press the camera button to take pictures.
3. Please turn off the Bluetooth Remote if you do not use it The blue light will go out when you turn off.
4. If the phone system is still within the scope of the Bluetooth remote control and still cannot be paired with it, please try restarting the phone. Make sure Bluetooth is turned off. After the phone restarts, turn on Bluetooth. Find the device name 'AB SHUTTER3.0' and connect. If you see the device name and aren't connected, try forgetting the device and try again.