

21

3.1.2.1 Manufacturer: Wuxi City Xiyou Motor Co., Ltd.
 3.1.2.2 Electronic motor code (as marked on the engine or other means of identification): SEG30C381PA000147
 3.3.3.4 15/30 minutes power: 1.0 kW at 2200 min⁻¹
 3.1.3.1 Manufacturer: N.A.
 3.1.3.2 Application code (as marked on the engine or other means of identification): N.A.
 3.3.1 Electric vehicle configuration: pure electric/hybrid-electric/mainpower-electric
 3.3.5.2 Category of hybrid electric vehicle: off-vehicle-charging/not-off-vehicle-charging
 3.9.2 Maximum assistance factor: N.A.

Maximum speed

1.8 Maximum speed of vehicle: 25 km/h (CV*: N.A.)
 3.9.3 Maximum vehicle speed for which the electric motor gives assistance: N.A.

Drive-train and control

3.5.3.9 Transmission (type): A
 3.5.4 Gear ratios: 10.37
 3.5.4.1 Final drive ratio: 10.37
 3.5.4.2 Overall gear ratio in highest gear: N.A.

Installation of tyres

6.18.1.1 Tyre size designation:
 Axle 1: 3.00-10, 42J Axle 2: 3.00-10, 42J
 Minimum Load capacity index:
 Axle 1: 16 Axle 2: 18
 Minimum speed category symbol:
 Axle 1: B Axle 2: B
 Recommended pressure:
 Axle 1: 250 kPa Axle 2: 250 kPa
 Rim size:
 Axle 1: 2.5*10 Axle 2: 2.5*10
 Sidecar wheel: N.A.

Bodywork

6.20.2.1 Door configuration and number of doors: N.A.
 6.16.1 Number of seating positions: 1
 6.16.1.1 Location and arrangement: r1, C1

Coupling devices

7.2.8 Type-approval number of coupling-device: N.A.

4.0.1 Environmental step: Euro 5 (34/5/5*)⁽¹⁾
 4.0.6 Sound level measured according to: N.A.
 4.0.6.1 Stationary: N.A. dB(A) (CV*: N.A.)
 4.0.6.2 Drive-by: N.A. dB(A) (CV*: N.A.)
 4.0.6.3 Limit value for L_{40m}: N.A. dB(A) (CV*: N.A.)

3.2.15 Exhaust emissions measured according to: N.A.
 3.2.15.1 Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable:

CO: N.A. mg/km (CV*: N.A.)
 THC: N.A. mg/km (CV*: N.A.)
 NMHC: N.A. mg/km (CV*: N.A.)
 NOx: N.A. mg/km (CV*: N.A.)
 HC+NOx: N.A. mg/km (CV*: N.A.)
 PM: N.A. mg/km (CV*: N.A.)

3.2.15.2 Type II test: tailpipe emissions at (increased) idle and free acceleration:
 HC: N.A. ppm at normal idling speed and: N.A. ppm at high idle speed (CV*: N.A.)
 CO: N.A. %vol at normal idling speed and: N.A. %vol at high idle speed (CV*: N.A.)
 3.2.15.3 Smoke corrected absorption coefficient: N.A.

Energy efficiency

4.0.2 Fuel consumption: N.A. l or kg/100km (CV*: N.A.)
 4.0.3 CO₂ emissions: N.A. g/km (CV*: N.A.)
 4.0.4 Energy consumption: 45 Wh/km (CV*: N.A.)
 4.0.5 Electric range: 50 km (CV*: N.A.)

Conversion of the performance of the vehicle:

8.1 Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no

Additional information:

9.1 Remarks: N.A.
 9.2 Exemptions: N.A.