

SWA12015/10



10

- 1. Standard digital audio signal between components
- 24 KHz at gold plated connector
- Cable shielded construction
- Plated brass contacts
- Copper braided reinforced aluminium shielding

11

- Formas de conectare de signal audio multiple intre las componente
- Conectare platinata la 24 kHz
- Conectare a aurilor 24K
- Sistem de protectie anti-ecou
- Blindaj cu plasă metalică reforțată pe oțel inoxidabil

12

- Erregler für Übertragung digitaler Audiosignale zwischen Komponenten
- 24 KHz goldplattete Kontakte
- 24K Goldplattete Kontakte
- Verbleibende Abschirmung
- Galvanische Entkopplung
- Isolierung des Aluminiumschirms durch Kupfergeflecht

13

- Forme de conectare de semnal digital intre las componente

14

- Standard audio digital signal between components
- 24 KHz at gold plated audio digital connector

15

- Digital audio signal between components

16

- Shielded digital audio signal between components

17

- Shielded digital audio signal between components

18

- Shielded digital audio signal between components

19

- Shielded digital audio signal between components

20

- Shielded digital audio signal between components

21

- Shielded digital audio signal between components

22

- Shielded digital audio signal between components

23

- Shielded digital audio signal between components



SWA12015/10

8670 000 15018

For an optimal experience, please use products at www.philips.com/welcome
©2005 Koninklijke Philips Electronics N.V.
All rights reserved. Made in China

