

Trio-Jet or Trio-Waterfall with Swivel installation manual

1. Adapter M22-M24 required?

The Trio-Jet or Trio-Waterfall with Swivel comes with an adapter that can be screwed onto the top of the Swivel to make it suitable for the larger M24 size with external threading so it can be screwed into the faucet. Equip the adapter when needed and place the large rubber washer on top of the plastic adapter. Make sure that the filter washer is in place before placing the adapter.

Without Adapter M22



With Adapter M24



2. Installation

The installation is very simple, just screw on the Trio-Jet / Trio-Waterfall onto or into your faucet. You can exert force onto the bottom part of Trio where you can select the flow-rate to make sure it is firmly attached.

3. What do in case of water leakages

Leaking is in most cases caused by missing / incorrect placement of the washer (metal touching metal will lead to water leakages) or that some part has not been screwed on tightly enough. First make sure that the filter washer and the thick rubber is in place in case the adapter is used. Secondly, make sure the product is screwed on tightly enough. Exert some force onto the bottom part of Trio until the product cannot be screwed on tighter.

If water is leaking from between the bottom part of the Trio and the Swivel, make sure that these parts are tightly connected. Firstly, hold the swivel and turn the bottom part clockwise to attach it more firmly. Secondly, check that the rubber washer is in place and in good condition. To check this, with one hand hold the swivel horizontally and with the other hand turn the bottom part counter clockwise. The bottom part will come off.

