

# PRODUCT INSTALLATION GUIDE



SIZE: 64\*64\*110(132)

## Parts list (According to the actual size; each type of screw and gasket have a spare)

Castores*5 pcs	Base*1 pc	Mechanism *1 pc	Armrest*1 pair
Seat cushion*1 pc	Backrest*1 pc	Headrest*1 pc	Samll shim 10+1 pcs
Hex wrench*1 pc	Big shim 3+1 pcs	Gaslift*1 pcs	Back plate screw (M8*45) 3+1pcs
Armrest screw / mechanism screw (M6*20)10+1pcs			

Note: before installing the chair, please sort the screws and measure the screw length for installation.

## Installation diagram (subject to actual size)

1 Put the castor into the base by pressing.	2 Insert the gaslift to the base.	3 Fix the armrest to the seat cushion with 6pcs samll shim and 6pcs(M6*20)screws, Pay attention to distinguish before and after.
4 Fix the mechanism to the seat cushion with 4pcs small shim and 4pcs(M6*20)screws. Pay attention to distinguish before and after.	5 Fix the back plate to the seat cushion with 3pcs big shim and 3pcs (M8*45)screws.	6 Put the upper part of chair to the gas lift.
7 Fix the headrest to the backrest .		



# Function diagram (subject to actual size)

