
TESY
It's impressive



BILIGHT HORIZONTAL

GCH 120 44 30 B12 TSR



TIN Code	305316
Model	BiLight 120 H
Real Volume	120 L
Height	0.440 m
Width	1.160 m
Depth	0.467 m
Rated power	3000 W
Mounting	Horizontal
Heating time Δt 45K (15 - 60°C)	2:05 h:min

Annual consumption of electricity AEC	2762 kWh
Energy class	C
Diameter	440 mm
Load profile	L
V40	181 L
$T_{out\ of\ the\ box}$	60 °C
MAX40	213 L
Design	Yes

Information

GCH 120 44 30 B12 TSR

Serie information

GCH 120 44 30 B12 TSR

In BiLight horizontal models* we are using the innovative TESY AquaMore Technology: REVOLUTIONARY SOLUTION FOR MORE HOT WATER

It provides up to 40%* more hot water for TESY BiLight horizontal models, compared to TESY BiLight horizontal models without this technology.

With this innovative technology, a horizontal TESY water heater delivers a comparable quantity of hot water as a vertical one.

- INSUTECH - an in-house TESY technology for highly efficient insulation and extremely low heat losses
- Bi light indication for easy and fast recognition of the work modes
- Electric on/off switch
- Freeze protection
- Glass-ceramic coating for corrosion protection
- Plasma-arc welding of the water tank for extended useful life

*For TESY BiLight Horizontal models with AquaMore Technology compared to TESY BiLight Horizontal models without this technology.

*BiLight Horizontal 50 L is not with TESY AquaMore Technology.