

SF-HTVR8104A-4K

Safire 5n1 DVR

4 CH HDTV / HDCVI / AHD / CVBS /
2 IP

4K/4 Mpx/5 Mpx/3Mpx (10fps in 4K,
20fps at 5 Mpx, 18fps at 3 Mpx, 25fps
at 4 Mpx/1080p)

Alarms (4/1) | 4 CH audio

HDMI 4K, VGA and BNC (CVBS)

output

Supports 1 hard disk



Safire

DVR 5n1

4Ch video HDTV/HDCVI/AHD/CVBS / 2 IP (extra) / 4Ch audio

H.265+/H.265/H.264+/H.264

Resolution per channel: 4K (10FPS) on TVI or 5Mpx (20FPS) or 3Mpx (18FPS) or 4Mpx/1080p (25FPS) in the rest of HD technologies

PTZ Control (RS485/Coaxial)

Alarms

HDMI 4K, VGA & CVBS Outputs

Mouse

Space for 1 HDD

Specifications

Brand	SAFIRE
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC, (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	4 Channels from BNC and 2 Channels IP (4K)
Video outputs	1 HDMI 4K, 1 VGA, 1 BNC (CVBS) Independent
Audio inputs	4 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Video / audio compression	H.265+ / H.265 / H.264+ / H.264 G.711u
Display resolution	4K (3840x2160, 2K (2560x1440), 1920x1080, 1280x1024, 1280x720, 1024x768
Recording resolution	4K on TVI / 5Mpx / 4Mpx / 3Mpx / 1080p / 720p
Main Stream coding	4K (10FPS) on TVI / 5Mpx (20 FPS) / 3Mpx (18 FPS) 4Mpx / 1080p / 720p / VGA / WD1 / 4CIF / CIF (25 FPS)
Extra Stream coding	WD1 / 4CIF / CIF (25 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	4 inputs / 1 relay
Video analysis	VCA: Line crossing Area intrusion
Recording method	Manual, programmed, motion detection, alarm
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 HDD SATA 3.5" of up to 8TB (not included)
Communication	RS485 (PTZ) / 2 x USB (Mouse and backup) / RJ45 10M/100M/1000M (Ethernet)
Remote access	Web browser, Smartphone App and Safire Control Center CMS Software
Power supply	DC 12V / 15W
Dimensions / Weight	45 (H) x 315 (W) x 242 (D) mm / 1.5 Kg