

SanDisk Extreme® Portable SSD

High-speed storage for hi-res photos and videos

Highlights

- High-speed transfers with up to 550MB/s read speeds**
- Save time moving hi-res photos and videos fast
- Rugged, water- and dust-resistant¹ (IP-55 rated)
- Shock-resistant solid state core for greater durability³
- Compact and pocket-sized
- Built by the SanDisk® brand, a technology leader and pioneer of the modern day SSD, to deliver superior performance

The rugged SanDisk Extreme® Portable SSD delivers high-speed transfers with up to 550MB/s read speeds**, making it perfect for saving and editing hi-res photos and videos. Its IP55 rating mean that it can stand up to rain, splashes, spills, and dust.¹ With up to 2TB capacity, it's perfect for extensive photo shoots, taking your portfolio with you or backing up your work. Compact and designed to fit in the palm of your hand, the SanDisk Extreme Portable SSD works with both PC and Mac computers and comes with a 3-year warranty.²



SanDisk Extreme* Portable SSD Specifications	
Available capacities:	250GB, 500GB, 1TB, 2TB
Dimensions (H x W x L):	0.348 x 1.951 x 3.787 in. (8.850 x 49.550 x 96.200 mm)
Operating temperature:	0°C to 45°C
Storage temperature:	-20°C to 70°C
Interface:	USB 3.1 Gen 2
Durability:	IP55-rated for water- and dust-resistance
Shock Resistant:	up to 1500G
Vibration Resistant:	5 gRMS, 10-2000 Hz
Warranty:	3-year; 3-year limited (US only)

For more information, please visit www.sandisk.com

SanDisk[®]

At SanDisk*, we're expanding the possibilities of data storage. For more than 25 years, SanDisk's ideas have helped transform the industry, delivering next generation storage solutions for consumers and businesses around the globe.

Western Digital Technologies, Inc. 951 SanDisk Drive | Milpitas | CA 95035 | USA

Western Digital Technologies, Inc. is the seller of record and licensee in the Americas of SanDisk® products.

- * IGB = 1,000,000,000 bytes. ITB = 1,000,000,000,000,000 bytes. Actual user storage less.

 ** Based on internal testing; performance may be lower depending on drive capacity, host device. OS and application. IMB = 1,000,000 bytes.

 ** IEC 60529 IP55. Tested to withstand water flow (30 kPa) at 3 min.; limited dust contact does not interfere with operation. Must be clean and dry before use.

 ** see www.sandisk.com/cut (up to 1500G) and vibration-resistant (5 gRMS, 10-2000 HZ), non-operating temperature (from -20°C to 70°C), operating temperature (from 0°C to 45°C).

SanDisk, the SanDisk logo, and SanDisk Extreme are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. All other marks are the property of their respective owners.

©2018 Western Digital Corporation or its affiliates. All rights reserved.