

GEP-2821 28-Port Gigabit PoE Switch, 24 PoE Outputs, 2 x Gigabit RJ45, 2 x Gigabit SFP, 802.3at/af PoE, 390W

Product Images





Short Description

- 24 Gigabit PoE ports, 2 Gigabit ports and 2 Gigabit SFP slots
- Total PoE power budget: 390W, up to 30W per port
- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- Supports DIP switch configuration for VLAN mode and Default mode features.
- Supports port-based VLAN
- 6KV surge protection, 6KV/8KV ESD protection.

Description

The GEP-2821 is LevelOne latest generation of 28-Port Gigabit Unmanaged PoE Switch, with 2 Gigabit RJ45 and 2 Gigabit SFP Uplink ports. also offers powerful DIP switch button configuration for VLAN mode and Default mode features. Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 1000Mbps. Increase the speed of your network backbone to a massive 56Gbps and bring Gigabit speeds all the way to your computers.

The GEP-2821 PoE-enabled switches features an IEEE 802.3af/at certified, better PoE functionality with 390W PoE power budget and usability. supports up to 24 ports at 15.4W, or 13 ports at 30 W to meet the increasing

power demands of users. giving you flexibility in power allocation for a variety of powered devices enabling you to scale your operations to meet business growth, operational cost savings, and ease of management.

Additional Information

Gigabit RJ45	2 Uplink ports (10/100/1000Base-T)
Gigabit SFP	2 Uplink ports (1000Base-X SFP slots)
802.3af/at PoE	24 Downlink ports (10/100/1000Base-T)
Color	Black
EAN	4015867223901
Model Number	GEP-2821
Grade	Commercial
Data rate	Gigabit Ethernet
PoE Supported	Yes
Manageable	No
Fanless	No
Concurrent ports	Total28.00
PoE Power Budget	Total390.00
Approval and Compliance	CE, RoHS
Operating humidity	0% RH ~ 90% RH
Operating temperature	-10°C ~ 50°C
Storage temperature	-40°C ~ 85°C
Package Contents	• GEP-2821 • Quick Installation Guide • Power Cord • 19" Rack Mount Kit
Product weight (kg)	4
Dimensions (W x D x H)	442 x 285 x 44 mm
MTBF	290,000 hrs (25°C)
Heat dissipation	119,544 (Btu/H)
Standards	• IEEE 802.3 10-BASE-T (Ethernet) • IEEE 802.3u 100-BASE-TX (Fast Ethernet) • IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) • IEEE 802.3z 1000BASE-X (Gigabit Ethernet) • IEEE 802.3 af/at
Power supply	AC100-240V, 50/60Hz
Pin assignment and polarity	1/2 (+), 3/6 (-)
Mount	19" rack mount, Desk mount
Flash memory size	4M
MAC address table	8K
Indicators	Power, Link/Act, PoE usage rate(20%, 40%, 60%, 80%, 90%)
Dip switch	VLAN mode, Default mode
Packet buffer	42Mpps
Backplane (Gbps)	56Gbps

