



Rendering and plastering mortar

Masonry mortar

University of Burgos

University of Burgos

19

19

EN 998-1 (2016)

EN 998-2 (2016)

Ordinary rendering mortar for exterior usage (GP)

Masonry mortar designed for ordinary usage (G) in exterior load-bearing constructions

| | |
|-------------------------------------|------------|
| Dry bulk density of hardened mortar | EN 1015-10 |
| Compressive strength at 28 days | EN 1015-11 |
| Adhesive strength | EN 1015-12 |
| Water absorption by capillarity | EN 1015-18 |
| Water vapour permeability (μ) | EN 1015-19 |
| Thermal conductivity | EN 1745 |
| Reaction to fire | EN 13501-1 |
| Workable life of fresh mortar | EN 1015-9 |
| Air content | EN 1015-7 |
| Freeze/thaw durability | |

| | |
|-------------------------------------|------------|
| Workable life of fresh mortar | EN 1015-9 |
| Water-soluble chloride content | EN 1015-17 |
| Air content | EN 1015-7 |
| Compressive strength at 28 days | EN 1015-11 |
| Initial shear strength | EN 1052-3 |
| Water absorption by capillarity | EN 1015-18 |
| Water vapour permeability (μ) | EN 1015-19 |
| Dry bulk density of hardened mortar | EN 1015-10 |
| Thermal conductivity | EN 1745 |
| Freeze/thaw durability | |
| Maximum aggregate size | EN 13501-1 |
| Reaction to fire | |