

C Operation Guidance & Led illumination

Press the switch button to check the capacity of Jump Starter

Indicator lights	1 Flashing	Full Flashing	1 solid	2 solid	3 solid	4 solid
Battery capacity	0%	10%	25%	50%	75%	100%

When charging, indicator lights will flash one by one. The number of solid indicator lights indicates the battery capacity of the Jump Starter. Full indicator lights are solid when charging is pause or complete.

D LED Operation

Long press the switch button for 3 seconds to start the LED illumination. The 4 modes of LED lights will appear in this sequence. 1. Normal, 2. Strobe, 3. SOS, 4. Off.

E Jump Starting a 12V Engine

1. Make sure the battery indicator lights display 3 lights
2. Connect the black battery clamp from the jumper cable to the vehicle's negative (-) battery terminal. Then connect the red battery clamp to the vehicle's positive (+) battery terminal.
3. Plug the power cable from the jumper into the start socket.
4. Start the vehicle
5. When the vehicle starts, remove the jumper cable power cord from the jump starter. Then disconnect the red clamp, and then the black clamp from the vehicle within 30 seconds.
6. Leave the vehicle's engine running



⚠ Never allow clamps touch each other or to contact the same piece of metal to prevent sparking

F The right way to remove the battery terminal cable



When it is time to remove the jumper power cable from the main unit follow these directions. Use your finger to hold and push the main unit (as shown on the picture to the right) to the opposite direction to help you pull the cable out.

G - Operation Guide

How to charge the jump starter's main unit

1. Plug the USB into a power source/block and / or plug into wall socket
2. Connect the micro usb to the jump starters main unit

- Charging Procedures

1. Make sure the mobile electronic device is 5V powered.
2. Connect the USB charging cable to the USB Power Port on the Power Bank
3. Choose the proper charger connector head for the mobile electronic device, and plug it into the mobile electronic device charging port.
4. Press the Power Button on the Battery ResQ to start charging the mobile device

- Charging mobile electronic devices

The power bank offers a USB charging cable with different types of charger connector heads to include (iPhone, iPad, Android, Tablets, and other DC 5V powered electronic devices.)

**Warning - Any other chargers will shorten the service life of the product and may damage the Jump Starter.

⚠ Any other chargers will shorten the product service life of the damage the Jump Starter

H TECHNICAL SPECIFICATIONS:

Size :	131*75*25mm
Weight :	225g
Output :	5V ≈2A, 12V Jump Start
Input :	12V ≈1A
Full charging time :	3 hours
Starting current :	200A
Peak current :	400A
Operating temperature :	0°C-60°C