

# ULTRA LIFE H11

Longer life and 4 year guarantee



### 4 year OSRAM guarantee

For a worry-free driving pleasure.  
Register online for fourth year:  
[www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)



### Extra lifetime

Up to four times longer lifetime  
compared to standard halogen lamps



### More durability

For longer replacement cycles and  
additional reliability and comfort



### The durable light with up to four times longer lifetime

OSRAM ULTRA LIFE automotive lamps are a favorite when it comes to durability. They have an impressive lifespan up to four times longer compared to standard halogen lamps and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). OSRAM provides a 4 year guarantee for the reliable ULTRA LIFE headlight lamps (fourth year with online registration, [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). In addition to this, ULTRA LIFE headlight lamps have a modern design with silver cap (H4/H7/H11). They are therefore ideal for frequent drivers or people who use daytime running lights, and can also be used in clear-glass headlights.

# Product datasheet

## Technical data

### Product information

Order reference	64211ULT
Application (Category and Product specific)	Halogen headlight lamp

### Electrical data

Power input	62 W <sup>1)</sup>
Nominal voltage	12.0 V
Nominal wattage	55.00 W
Test voltage	13.2 V

<sup>1)</sup> Maximum

### Photometrical data

Luminous flux	1350 lm
Luminous flux tolerance	±10 %
Color temperature	3200 K

### Dimensions & weight



Diameter	12.0 mm
Product weight	22.56 g
Length	67.0 mm

### Lifespan

Lifespan B3	1000 h
Lifespan Tc	2000 h

### Additional product data

Base (standard designation)	PGJ19-2
-----------------------------	---------

## Product datasheet

### Capabilities

Technology	HAL
------------	-----

### Certificates & standards

ECE category	H11
--------------	-----

### Country specific categorizations

Order reference	64211ULT
-----------------	----------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4050300602387   4052899431164   4052899436114   4052899436138   4052899436510   4052899436190   4052899436473   4052899436176   4052899436275
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work



Others graphics

### Logistical Data




Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899431164	ULTRA LIFE H11	Folding carton box 1	33 mm x 37 mm x 71 mm	0.09 dm <sup>3</sup>	29.00 g
4052899431171	ULTRA LIFE H11	Bundle 10	- x - x -		

## Product datasheet

4052899431188	ULTRA LIFE H11	Shipping carton box 100	341 mm x 191 mm x 154 mm	10.03 dm <sup>3</sup>	3101.00 g
4052899436473	ULTRA LIFE H11	Blister 1	135 mm x 95 mm x 40 mm	0.51 dm <sup>3</sup>	34.00 g
4052899436480	ULTRA LIFE H11	Shipping carton box 10	279 mm x 115 mm x 146 mm	4.68 dm <sup>3</sup>	423.00 g
4052899436510	ULTRA LIFE H11	Hard Cover Box 2	114 mm x 48 mm x 106 mm	0.58 dm <sup>3</sup>	138.00 g
4062172062114	ULTRA LIFE H11	Shipping carton box 10	268 mm x 126 mm x 125 mm	4.22 dm <sup>3</sup>	775.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File	
	Brochures 724901_ULTRA LIFE Leaflet EN
	Product movie 724899_ULTRA LIFE Trailer EN
	360 Degree Image ULTRA LIFE H11 64211ULT

### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM