

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements

Date: 2019/01/30





EU Type Examination Certificate

n. 158190517/OE

Validity: 2024/01/29

This Certificate cancels & replaces the previous one n° 158171602/OE dated 2017/04/21

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	G <mark>RISPORT SpA calzatur<mark>ificio</mark> 31030 CASTELCUCCO (TV) – Via Erega, 1 – ITALIA</mark>
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)
Category of PPE:	II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.
Model	"0033253-70211"
Description:	design: B (ankle shoe); fastening system: by means of laces; processing: direct injection; outsole: black rubber marked "SAFETY VERA GOMMA HRO OLL RESISTANT ANTISTATIC MADE IN ITALY ABS ANTISHOCK", (cod. 2137BCP/00 022/ 1/00); midsole: colfie-colored foamed PU (cod. MPI/001); scuff-resistant covering of the toe region: made of the same material of the midsole; upper: black leather DAKAR TREKKING IDRO declared thickness 2,0/2,2 mm (cod DAI/NER), with inserts in the heel area made of grey retro-reflective material MOON LIGHT (cod. MOX/47)with a reinforcement in the heel area in black polymeric materia SUPPORT SYSTEM (cod. G016NG); collar: fabric VANCOUVER in black color 4017 with a white hatching matched with PE40 (cod. VAA/4017); tongue/bellows: simple fabric VANCOUVER in black color 4017 with a white hatching (cod. VAN/4017), lined and centrally padded; vamp and rear lining: fabric SPOTEX TEPOR SELENE in black color (cod. SPO/SELN), which covers the insole; collar lining: fabric ZP01/1500 (cod. LC/ZP01) covered by the lining, which also serves as penetration resistant insert; removable insock: black foam material matched with non-woven fabric in contact with the foot, perforated in the forepart, with an aluminum insert stitched with antistatic thread (zigzag stitching), and an insert in piglet nabuk leather in otter-like color (cod CIF/LON) stitched in the heel area in contact with the foot (cod. FLNPLCA); toecap: in perforated and reinforced steel article 604FR (cod. 604ACRF).
Technical Standard:	EN ISO 20344:2011Personal protective equipment – Test methods for footwear(UNI EN ISO 20344:2012)Personal protective equipment – Safety footwear(UNI EN ISO 20345:2011)Personal protective equipment – Safety footwear
Intended use:	general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.
Size range:	from 39 to 47
Technical File:	DC-9526/E + DC-8293/E





PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2019/01/30

n. 158190517/OE

Validity: 2024/01/29

Test report:	RCT n°361607/E
Functions and performance levels:	 basic requirements for safety footwear (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which: SRC = Slip resistance – meets the following requirement: <u>surface</u>: ceramic / <u>lubricant</u>: detergent solution; <u>surface</u>: steel / <u>lubricant</u>: glycerol.
	Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): S3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole; HRO = resistance to hot contact of the outsole; HI = heat insulation of sole complex; WR = resistance to water penetration of the whole footwear.
	Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).
	 CE Marking; Name of the Manufacturer (on the external side of the footwear); designation, unique and unambiguous, of the footwear; nr. and year of the Standard of reference + safety symbols; size of footwear (printed also into the outsole); production date (month + year); additional information: internal codes.
C E ^U 12 0033253-702	NI EN ISO 0345:2012 2 / 2016

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

Marco/Meyer Managing Director



2/2