

## DS-2CD2346G2-I(U)

### AcuSense 4 MP IR Fixed Turret Network Camera



- High quality imaging with 4 MP resolution
- Excellent low-light performance with powered-by-DarkFighter technology
- Clear imaging against strong back light due to 120 dB WDR technology
- Efficient H.265+ compression technology
- False alarm reduction through human and vehicle target classification based on deep learning
- -U: Built-in microphone for real-time audio security
- -U: Water and dust resistant (IP66); -I: Water and dust resistant (IP67)

### AcuSense

Empowered by deep learning algorithms, Hikvision AcuSense technology brings human or vehicle target classification alarms to front- and back-end devices. The system can greatly reduce false alarms generated by targets other than humans or vehicles, vastly improving alarm efficiency and effectiveness.



## ▪ Specification

| Camera                      |  |
|-----------------------------|--|
| Image Sensor                | 1/2.7" Progressive Scan CMOS   |
| Min. Illumination           | Color: 0.003 Lux @ (F1.4, AGC ON)  |
| Shutter Speed               | 1/3 s to 1/100,000 s   |
| Day & Night                 | ICR Cut  |
| Slow Shutter                | Yes  |
| Angle Adjustment            | Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°   |
| P/N                         | P/N  |
| Wide Dynamic Range          | 120 dB   |
| Lens                        |  |
| Lens Type & FOV             | 2.8 mm, horizontal FOV 103°, vertical FOV 55°, diagonal FOV 123°<br>4 mm, horizontal FOV 83°, vertical FOV 45°, diagonal FOV 98°<br>6 mm, horizontal FOV 53°, vertical FOV 28°, diagonal FOV 62° |
| Aperture                    | F1.4   |
| Lens Mount                  | M12  |
| Aperture Type               | Fixed  |
| Illuminator                 |  |
| IR Range                    | Up to 30 m   |
| Wavelength                  | 850 nm   |
| Smart Supplement Light      | Yes  |
| Supplement Light            | IR   |
| Video                       |  |
| Max. Resolution             | 2592 × 1944  |
| Main Stream                 | 50Hz: 20fps (2592 × 1944)<br>25fps (2688 × 1520, 2304 × 1296, 1920 × 1080, 1280 × 720)<br>60Hz: 20fps (2592 × 1944)<br>30fps (2688 × 1520, 2304 × 1296, 1920 × 1080, 1280 × 720)                 |
| Sub Stream                  | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)<br>60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)   |
| Third Stream                | 50Hz: 25fps (1280 × 720, 640 × 480, 640 × 360, 360 × 240)<br>60Hz: 30fps (1280 × 720, 640 × 480, 640 × 360, 360 × 240)   |
| Video Compression           | Main stream: H.265/H.264<br>Sub-stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264   |
| Video Bit Rate              | 32 Kbps to 8 Mbps  |
| H.264 Type                  | Baseline Profile/Main Profile/High Profile   |
| H.265 Type                  | Main Profile   |
| H.264+                      | Main Stream supports   |
| H.265+                      | Main Stream supports   |
| Bit Rate Control            | CBR/VBR  |
| Scalable Video Coding (SVC) | Yes  |
| Region of Interest (ROI)    | 1 fixed region for each stream   |
| Audio                       |  |
| Environment Noise Filtering | -U: Yes  |

|  |   |
|--|---|
| Audio Sampling Rate                          | -U: 8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz   |
| Audio Compression                            | -U: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3   |
| Audio Bit Rate                               | -U:<br>64Kbps(G.711ulaw/G.711alaw)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)/<br>8-320Kbps(MP3)   |
| <b>Network</b>                               |   |
| Simultaneous Live View                       | Up to 6 channels  |
| API  | ONVIF (PROFILE S, PROFILE G, PROFILE T), ISAPI, SDK   |
| Protocols                                    | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS   |
| Smooth Streaming                             | Yes   |
| User/Host                                    | Up to 32 users. 3 user levels: administrator, operator and user   |
| Security                                     | Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.2, WSSE and digest authentication for ONVIF               |
| Network Storage                              | MicroSD/SDHC/SDXC card (256 GB) local storage, and NAS (NFS, SMB/CIFS), auto network replenishment (ANR)<br>Together with high-end Hikvision memory card, memory card encryption and health detection are supported |
| Client                                       | iVMS-4200, Hik-Connect, Hik-Central   |
| Web Browser                                  | Plug-in required live view: IE8+, Chrome 41.0-44, Firefox 30.0-51, Safari 8.0-11<br>Plug-in free live view: Chrome 57.0+, Firefox 52.0+   |
| <b>Image</b>                                 |   |
| Day/Night Switch                             | Day, Night, Auto, Schedule  |
| Image Enhancement                            | BLC, HLC, 3D DNR  |
| Image Parameters Switch                      | Yes   |
| Image Settings                               | Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance adjustable by client software or web browser  |
| <b>Interface</b>                             |   |
| Audio  | -U: 1 built-in microphone   |
| On-board Storage                             | Built-in micro SD slot, up to 256 GB  |
| Hardware Reset                               | Yes   |
| Communication Interface                      | 1 RJ45 10M/100M self-adaptive Ethernet port   |
| <b>Intelligent (Traditional Algorithm)</b>   |   |
| Basic Event                                  | Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error), scene change detection  |
| <b>Intelligent (Deep Learning Algorithm)</b> |   |
| Face Capture                                 | Yes   |
| Premier Protection                           | Line crossing detection, intrusion detection, region entrance detection, region exiting detection   |
| <b>General</b>                               |   |
| Storage Conditions                           | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)   |
| Startup and Operating Conditions             | -30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)   |
| Power Supply                                 | 12 VDC ± 25%, reverse polarity protection<br>PoE: 802.3af, class 3  |

|                               |   |
|-------------------------------|---|
| Power Consumption and Current | 12 VDC, 0.48 A, max. 5.8 W<br>PoE: (802.3af, 36 V to 57 V), 0.19 A to 0.12 A, max. 6.8 W  |
| Power Interface               | Ø5.5 mm coaxial power plug  |
| Material                      | Metal except for trim ring  |
| Camera Dimension              | Ø138.3 × 126.3 mm (5.4" × 5.0")   |
| Package Dimension             | 170 × 170 × 150 mm (6.7" × 6.7" × 5.9")   |
| Camera Weight                 | Approx. 770 g (1.7 lb.)   |
| With Package Weight           | Approx. 1073 g (2.4 lb.)  |
| Linkage Method                | Upload to NAS/memory card, notify surveillance center, trigger record, trigger capture  |
| Web Client Language           | 33 languages<br>English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian |
| General Function              | Anti-flicker, heartbeat, mirror, privacy masks, flash log, password reset via e-mail, pixel counter   |
| Software Reset                | Yes   |
| <b>Approval</b>               |   |
| EMC                           | FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016); KC (KN 32: 2015, KN 35: 2015)  |
| Safety                        | UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013); BIS (IS 13252(Part 1):2010+A1:2013+A2:2015); LOA (IEC/EN 60950-1)   |
| Environment                   | CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)   |
| Protection                    | -U: Ingression protection: IP66 (IEC 60529-2013)<br>-I: Ingression protection: IP67 (IEC 60529-2013)  |

## Available Model

DS-2CD2346G2-I (2.8 mm, 4 mm, 6 mm)

DS-2CD2346G2-IU (2.8 mm, 4 mm, 6 mm)

## Dimension



## ▪ Accessory



DS-1276ZJ-SUS  
Corner Mount



DS-1271ZJ-140  
Pendent Mount



DS-1273ZJ-140B  
Wall Mount



DS-1275ZJ-SUS  
Vertical Pole Mount



DS-1280ZJ-DM21  
Junction Box



DS-1273ZJ-140  
Wall Mount

Distributed by



## HIKVISION

### Headquarters

No.555 Qianmo Road, Beijing District,  
Hangzhou 310051, China  
T +86-571-8807-5888  
overseas@business@hikvision.com

**Hikvision USA**  
T +1-909-895-8400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-29489800  
sales@prmahikvision.com

**Hikvision Canada**  
T +1-866-205-8880  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5642770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55-11-3318-0050  
latam.support@hikvision.com

**Hikvision Turkey**  
T +90-1218521-7070-7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7852-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-862140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27-1101-0351170  
sales.africa@hikvision.com

**Hikvision France**  
T +33011-65-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730067  
nikla.punrtov@hikvision.ru

**Hikvision Vietnam**  
T +84-874270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6884-6718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-15-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-67-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-609-67-89  
salesru@hikvision.com

**Hikvision Korea**  
T +82-10331-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933769  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com