

DIGITUS Ultra Slim HDMI® splitter, 1x4, 4K / 60 Hz

DS-45323
EAN 4016032465065



Ultra Slim HDMI Splitter, 1x4, 4K/60Hz HDR, HDCP 2.2, 18 Gbps, Micro USB powered

Splits an HDMI signal on four displays - supports UHD 4K / 60 Hz with HDR

- Supports HDMI® resolutions of up to 4K / 60 Hz (4096 x 2160p)
- Data transfer rate: 18 Gbps (6 Gbps per channel)
- Supports: RGB 4:4:4 / YCbCr 4:4:4 / YCbCr 4:2:2 / YCbCr 4:2:0
- Supports 36bit Deep Color (12 Gbps per channel)
- Supports HDCP 2.2 / 1.4
- Supports: 3D
- Supports: HDR (High Dynamic Range)
- Supports cascading of up to 8 splitters
- Operating temperature: 0°C ~ 45°C
- Operating humidity: 10% - 85% RH (non-condensing)
- Power consumption: 2.5 W (5 V / 0.5 A)

- ESD protection: +/- 8 kV air insulation discharge, +/- 4 kV contact discharge
- Housing: Metal
- Color: Black
- Weight: 80 g
- Dimensions: L 11.2 x W 4 x H 0.9 cm
- Video connection ports: HDMI
- Number of ports: 4
- HDTV Resolution max.: 4096 x 2160 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Signal input: HDMI
- Signal output: HDMI

Package contents

- Ultra Slim HDMI Splitter, 1x4, 4K / 60 Hz
- USB A on Micro USB connection cable (power supply)
- User manual

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 20 | 7.00 | 32.00 | 52.00 | 17.50 | 29,120.00 |
| Packaging Unit Inside | 1 | 0.35 | 11.00 | 15.00 | 2.50 | 412.50 |
| Packaging Unit Single | 1 | 0.35 | 11.00 | 15.00 | 2.50 | 412.50 |
| Net single without Packaging | 1 | 0.25 | 11.00 | 15.00 | 2.50 | 412.50 |

More images:



