

AMM
AMM
2.5A 250V

Desktop Charger DC465PD

Model: 1001-0141

PRI: 110-240 V ~ 50-60 Hz max 1.5 A

SEC: USB-C1: 5.0 V = 3.0 A 15.0 W

USB-C1: 9.0 V = 3.0 A 27.0 W

USB-C1: 12.0 V = 3.0 A 36.0 W

USB-C1: 15.0 V = 3.0 A 45.0 W

USB-C1: 20.0 V = 3.25 A 65.0 W

USB-C2: 5.0 V = 3.0 A 15.0 W

USB-C2: 9.0 V = 2.0 A 18.0 W

USB-C2: 12.0 V = 1.5 A 18.0 W

USB-A1: 5.0 V = 3.0 A 15.0 W

USB-A1: 9.0 V = 2.0 A 18.0 W

USB-A1: 12.0 V = 1.5 A 18.0 W

USB-A2: 5.0 V = 3.0 A 15.0 W

USB-A2: 9.0 V = 2.0 A 18.0 W

USB-A2: 12.0 V = 1.5 A 18.0 W

USB-C1 & C2: C1 Max. 20.0 V = 1.5 A 30.0 W

USB-C1 & C2: C2 Max. 12.0 V = 1.5 A 18.0 W

USB-C1 & C2 & A1/A2: C1 Max. 20.0 V = 1.5 A 30.0 W

USB-C1 & C2 & A1/A2: C2/A1/A2 shared Max. 5.0 V = 3.0 A 15.0 W

ANSMANN AG, Industriestr. 10, 97959 Assamstadt, Germany



HARLOW
CM19 5QB

Made in China

CDBC