## 1. Safety Precautions

This product complies with the requirements of the following directives of the European Union for CE conformity: 2014/30/ EU (electromagnetic compatibility), 2011/65/EU (RoHS), 2009/125/EC (Ecodesign Directive).Pollution degree 2.

To ensure safe operation of the equipment and eliminate the danger of serious injury due to short-circuits (arcing), the following safety precautions must be observed.

Damages resulting from failure to observe the following safety precautions are exempt from any legal claims whatever.

- \* Do not operate the meter before the cabinet has been closed and screwed safely.
- \* Check test leads and probes for faulty insulation or bare wires before connection to the equipment.
- \* Comply with the warning labels and other info on the equipment.
- \* Keep the equipment dry.
- \* Do not subject the equipment to direct sunlight or extreme temperatures, humidity or dampness.
- \* Do not subject the equipment to shocks or strong vibrations.
- \* Let the equipment stabilize at room temperature before measurement (important for exact measurements).
- \* Replace the battery as soon as the battery indicator "BAT" appears. With a low battery, the meter might produce false reading that can lead to personal injury.
- \* Fetch out the battery when the meter will not be used for long period.
- \* The meter is suitable for indoor use only
- \* Do not store the meter in a place of explosive, inflammable substances.
- \* Do not modify the equipment in any way
- \* Opening the equipment and service and repair work must only be performed by qualified service personnel
  - 16