



by Honeywell

LASER LITE®

0 33552002031

LL-1

200 PR / UNCORDED

COUNTRY OF ORIGIN: US

20 281 0923 2

NRR 32 / Canada Class A(L) / SLC₈₀ 25, Class 4 / SNR 35

Size 6-11 mm

Noise Reduction Rating	32 DECIBELS
WHEN USED AS DIRECTED	
THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30. (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)	
HONEYWELL SAFETY PRODUCTS USA, INC. SAN DIEGO, CA 92154 MODEL NO. LL-1 / LL-30	
Federal law prohibits removal of this label prior to purchase	
	LABEL REQUIRED BY U.S. E.P.A. REGULATION 40 CFR Part 211, Subpart B

Certified Product

Australian Standard
AS/NZS 1270 Lic. 1679
SAI Global

AU/NZ
Hearing protector class 4 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise up to 105 dB(A) assuming an 85 dB(A) criterion. A lower criterion may require a higher protector class.

SNR
35 dB

H = 34 dB
M = 32 dB
L = 31 dB

