



**WIRE ADDRESS**

P1	P2	P1	P2
1	1	14	14
2	2	15	15
3	3	16	16
4	4	17	17
5	5	18	18
6	6	19	19
7	7	20	20
8	8	21	21
9	9	22	22
10	10	23	23
11	11	24	24
12	12	25	25
13	13	Shell	Shell

- Electrical Test:
- 1.100% TEST OPEN SHORT MIS-WIRE.
  - 2.CONTACT RESISTANCE:3Ω MAX.
  - 3.INSULATION RESISTANCE:5MΩ MIN.
  - 4.HI-POT:300V DC/10MS.

NUMBER	1	2	4	Quantity	Unit
D	45P PVC BEIGE			6	
C	Screw:#4-40UNC(Nickel Plated,Beige)			4	PCS
B	DB 25P MALE(Blue Insulator, Nickel Plated)			2	PCS
A	NON-UL 30AWG*25C+AD,OD=7.0mm BEIGE PVC JACKET.			1	PCS
PRODUCT SPECIFICATIONS					
ROLINE RS-232 Cable, DB25 M - M, 4.5m					
Item		11.01.3545			
Draw		Shabe		Date: 2020.05.13	
Approval					
Duty		F16		BOM.NO.:13888	
Sample NO.					
Drawings of 1 (2)					
Proportion: 1:1					
Unit(mm)					
A4					

