


● SPECIFICATIONS ● TECHNISCHE EINZELHEITEN ● SPÉCIFICATIONS ● DATI TECNICI ● ESPECIFICACIONES ● ESPECIFICAÇÕES ● ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ ● الموصفات

Model Modell Modèle Modello Modelo Model Модель الموديل	Size Größe Puissance continue (RMS) Taille Dimensioni Tamaño Tamaño Размер القياس	Continuous power handling (RMS) Maximale Leistung (RMS) Puissance continue (RMS) Max. Musikleistung Potencia continua (RMS) Gestión continua de la potencia (RMS)	Maximum power Max. Musikleistung Puissance musicale maximum Impedance nominale Potencia máxima de musica	Nominal impedance Nomimpedanz Impédance nominale Impedenza nominale Impedancia nominal	Sensitivity Empfindlichkeit Sensibilité Sensibilità Sensibilidad	Frequency response Frequenzgang Bande passante Risposta alla frequenza Respuesta de frecuencia	Magnet weight Magnetgewicht Poids aimant Peso del magnete Peso do iman	Displacement Wegamplitude Déplacement Spostamento Desplazamiento	Revc (Ω)	Levc (mH)	Fs (Hz)	Qms	Qes	Qts	Vas (liters) (cuft)	Rms (N.s/m)	Mms (g)	Cms (mN)	Diam (mm) (inch)	BL (T.Jn)	Xmax	
TS-A300S4	30 cm (12")	500 W	1 500 W	4 Ω	77 dB (1 W / 1 m)	20 Hz To 2.3 kHz (-20 dB)	1 700 g (60 oz)	1.54 liters (0.054 cuft)	4.4	4.86	26	7.22	0.67	0.62	75.0 2.65 2.01 3.07	4.24	188	20.0×10^{-5}	256 10.1 258 17.7 (8 Ω)	14.1	10.7 0.42 0.40	
TS-A300D4 / A1200D4	30 cm (12")	500 W	1 500 W	dual 4 Ω	77 dB (1 W / 1 m)	20 Hz To 2.3 kHz (-20 dB)	1 700 g (60 oz)	1.54 liters (0.054 cuft)	dual 4.3	7.73 (8 Ω) 1.93 (2 Ω)	25	5.62	0.78	0.69	4.95	181	23.3×10^{-5}	10.1 258 17.7 (8 Ω) 10.1 6.9 (2 Ω)	14.1	0.42 0.40		
TS-A250S4	25 cm (10")	400 W	1 300 W	4 Ω	73 dB (1 W / 1 m)	20 Hz To 2.0 kHz (-20 dB)	1 600 g (56 oz)	0.74 liters (0.026 cuft)	3.7	3.84	30	4.42	0.60	0.52	34.1 1.20	5.84	136	20.5×10^{-5}	209 12.6 8.2	11.3 0.44	16.1 (8 Ω) 8.0 (2 Ω)	10.8 0.43
TS-A250D4	25 cm (10")	400 W	1 300 W	dual 4 Ω	74 dB (1 W / 1 m)	20 Hz To 2.0 kHz (-20 dB)	1 600 g (56 oz)	0.74 liters (0.026 cuft)	dual 3.7	6.53 (8 Ω) 1.63 (2 Ω)	30	4.27	0.68	0.59	36.6 1.29	5.65	128	22.0×10^{-5}	209 8.2	16.1 (8 Ω) 8.0 (2 Ω)	10.8 0.43	

● HOW TO INSTALL ● EINBAU ● MODE D'INSTALLATION ● MODO DI INSTALLAZIONE
● INSTALACION ● COMO INSTALAR ● KAK PODKLOUCHITЬ ● كيفية التركيب



Model Modell Modèle Modello Modelo Model Модель الموديل	Cutout hole Öffnung Orifice de découpe Foro prestampato Furo de corte Монтажное отверстие الفتحة المعدة لقطع	Mounting depth Einbauteufe Profondeur d'enca斯特rement Profondità di montaggio Profundidad de montaje Profundidade de montagem Глубина установки عمق الشبورة	Height Höhe Hauteur Altezza Altura Altura Высота ارتفاع
TS-A300S4 / TS-A300D4 / TS-A1200D4 TS-A250S4 / TS-A250D4	φ281 (11-1/8 Dia.) φ230 (9 Dia.)	147 (5-3/4) 133 (6-1/4) mm (in.)	164 (6-1/2) 149 (5-7/8)

