ZEN One Signature

...d your zen

...l-purpose digital audio hub – delivers exceptional sound from every digital device in a home ...dio environment

...e DAC, universal connectivity – Bluetooth, USB and S/PDIF inputs

...rist engineering and Signature-grade circuitry – performance-tuned for captivating sound ...h all forms of media, from hi-res music to movie and video game soundtracks

...TURES:

...uetooth

...t-generation HD Bluetooth technology ensures the best sound from every source

...ensive high-definition codec support – aptX HD, aptX Adaptive, LDAC and HWA/LHDC

...l engine

... Native hi-res DAC – supports 32-bit/384kHz PCM and fully native DSD

...erful 16-core XMOS processor – performs full MQA decoding (to 384kHz)

...raded GMT femto-precision clock and customised digital filter eradicate jitter and other ...s of digital distortion

...cal and coaxial S/PDIF digital outputs support 32-bit/192kHz PCM and MQA

...gue stage

...nced circuit design with Signature-grade circuit components delivers ultra-low distortion ...xceptional sonic purity

...m Pentaconn balanced and RCA single-ended analogue outputs – connect to an integrated ...preamp, headphone amp or active speakers

...TENTS:

...N One Signature
...A Cable
...struction card
- 1 x iFi iPower2
- 1 x Antenna
- 1 x USB3.0 Cable
- 1 x User Manual

SPECIFICATIONS:

Power:	DC 5V (centre pin +ve)
Digital inputs:	USB3.0 Type B (USB2.0 compatible)
	S/PDIF (coaxial, TOSLINK optical)
	Bluetooth 5.1™ (aptX, aptX HD, aptX A...
	LHDC/HWA, AAC and SBC codec)
Formats:	
PCM	44.1/48/88.2/96/176.4/192kHz
DSD	2.8/3.1/5.6/6.1/11.3/12.3MHz
DXD	352.8/384kHz
MQA	Decoder
Bluetooth:	96kHz
Chipset:	Bit-Perfect DSD & DXD DAC by Burr B...
	Qualcomm QCC 5100 Series
Analogue outputs:	Coaxial, Audio RCA L/R
	4.4 Balanced Lineout
Frequency Response:	5Hz - 80kHz ±3dB
Outputs:	4V / 2V max. (BAL/UnBAL)
Output Impedance:	≤72Ω/36Ω (BAL/UnBAL)
SNR:	-105dB(A) @ 0dBFS (BAL/UnBAL)
THD + N:	<0.002% @ 0dBFS (BAL/UnBAL)
Power consumption:	No Signal ~0.7W/Max Signal ~1W
Dimensions:	158 x 100 x 35 mm
	6.2" x 3.9" x 1.4"
Net weight:	485g (1.1 lbs)
Warranty period:	12 months

Specifications are subject to change without notice.

5 060738 785612

안전인증번호:
Certificate No.
R-R-iFi-ZENOneSig

Technology licensed from AMR (UK).
Assembled in China.
Ver1.2

CE REP
ABBINGDON EU BV
Mercatorweg 28 Arnhem 6827 DC Netherlands

iFi audio

ZEN C...
531