

# VS182A/VS184A

## 2/4-Port HDMI Splitter

- The VS182A/VS184A HDMI Splitter is the perfect solution for anyone who needs to send one source of digital high definition video to two (VS182A) or four (VS184A) displays at the same time. It supports all HDMI-enabled equipment, such as DVD players, satellite set-top boxes and all HDMI displays.


The VS182A/VS184A HDMI Splitter is HDCP (High Bandwidth Digital Content Protection) compliant, making it effective for use with all HDMI displays in home theater applications, as well as in corporate, educational and commercial settings.

**HDMI™**  
HIGH DEFINITION MULTIMEDIA INTERFACE



### Features

- Connects one HDMI source to two (VS182A), four (VS184A) HDMI displays at the same time
- HDMI (3D, Deep Color, 4kx2k); HDCP Compatible
- Supports resolutions of up to Ultra HD 4kx2k and 1080p Full HD
- Supports Dolby True HD and DTS HD Master Audio
- Long distance transmission – up to 15 m (24 AWG)
- Supports up to 340MHz bandwidth for high performance video
- Signaling rates up to 3.4 Gbits in support of 1080p display
- Plug-and-play – no software installation required



### Specification

Function		VS182A	VS184A
Display Connections		2	4
Connectors	Device	1 x HDMI Type A Female (Black)	
	Display	2 x HDMI Type A Female (Black)	4 x HDMI Type A Female (Black)
Power		1 x DC Jack	
LEDs	Power	1 (Orange)	
	Input	1 (Green)	
	Output1	1 (Green)	
	Output2	1 (Green)	
	Output3	N/A	1 (Green)
HDMI Resolution		4k2k, 1080p	
Power Consumption		DC5.3V, 2.0W	DC5.3V, 4.6W
Environment	Operating Temp.	0-50°C	
	Storage Temp.	-20°C - 60°C	
	Humidity	0-80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	0.31 kg	0.47 kg
	Dimensions (L x W x H)	12.50 x 8.00 x 2.50 cm	20.00 x 8.00 x 2.50 cm

