

USB LAN


- Network Speed: 10Mbps or 100Mbps automatically
- Connectors: 1 x RJ-45 Shielded Phone Jack

Features:

- Integrated Fast Ethernet MAC, Physical Chip and transceiver in one chip
- Supports 10 Mb/s and 100 Mb/s N-Way Auto-negotiation operation
- Compliant to USB interface Version 1.0/1.1/2.0
- Full-Speed(12Mb/s) USB Device
- Support all USB standard command
- Supports Suspend/Resume detection logic
- Supports 4 endpoints
 - 1.1 control endpoint with maximum 8-byte packet
 - 2.1 bulk In endpoint 64 bytes/packet
 - 3.1 bulk Out endpoint with 64 bytes/packet
 - 4.1 interrupt In endpoint with 8 bytes/packet
- 18K bytes SRAM built in.(2k bytes for Tx buffer, and 16K bytes for Rx buffer)
- Uses 24C02 to store resource configuration, ID parameter, etc
- Half/Full duplex 10/100Mbps operation

Importer:

APTEL Adam Pawlak sp. j.
ul. Produkcyjna 106B
16-680 Białystok



Instalacja dostępna za <http://www.apitel.pl>

(IEEE802.3u)

Producent:

Shenzhen Transshow Industrial Ltd
Address: Busha Lu NO.283, Bujia,
Shenzhen, China