

14 Technical data

All wine refrigerators	
Rated Power Suppl	220 – 240V – / 50Hz / 1P
Climate Class	SN – ST
Storage Temperature Range	5 – 20°C / 41 – 68°F
Intended ambient temperature use	3 – 38 °C / 37 – 100 °F
Wine Storage Compartment Humidity	50% – 80%
Compressor or Thermoelectric System	Compressor (Reciprocating)
Defrosting	Automatic
Cooling Type	Fan Cooling
Refrigerant Type	R600a
Foaming Agent of Polyurethane	Cyclopentane
Power Cord	1.8 m, Black, Schuko Plug

Test/certificates



	B29G	B68G	B162S	B195S
Size (width - bottles)	30 cm - 20	60 cm - 54	60 cm - 100	60 cm - 125
Total Gross/Storing Volume (l)	62/57	152/134	310/262	380/335
Max. Bottles with Sliding/Storage Shelves	20/29	52/68	102/162	126/195
Number of Compartment	1	1	1	1
Wine Conditioning System	Single	Single	Single	Single
Number of Doors	1	1	1	1
Default Opening	Left	Left	Left	Left
Door Opening Angle	180°	180°	110°	110°
Shelves	2 Fixed	2 Fixed	3 Fixed	4 Fixed
Sound Power Level (LWA - db(A) re 1 pW)	40	42	42	42
Current (A)	0.6	1.2	1.4	1.4
Power Input (W)	85	100	160	160
Heater Winter System (W)	≤80	≤120	≤120	≤120
Display Position	Outside Top Front	Outside Top Front	Inside Behind Door	Inside Behind Door
Interior Light	0.15 W LED White	2x 0.15 W LED White	2x 0.15 W LED White	2x 0.15 W LED White
Installation Type	Built-Under/ Freestanding	Built-Under/ Freestanding	Built-In/Recessed/ Freestanding	Built-In/Recessed/ Freestanding
Adjustable Feet (mm)	80	15 – 80	80	80
Dimensions (W×H×D mm/inches)	295 x 863 x 615 / 11 ³ / ₄ x 34 x 24 ¹ / ₄	595 x 863 x 615 / 23 ¹ / ₂ x 34 x 24 ¹ / ₄	595 x 1476 x 615 / 23 ¹ / ₂ x 58 ¹ / ₈ x 24 ¹ / ₄	595 x 1768 x 615 / 23 ¹ / ₂ x 69 ¹ / ₈ x 24 ¹ / ₄
Carton Dimensions (W×H×D mm/inches)	326 x 920 x 628 12 ³ / ₄ x 36 ¹ / ₄ x 24 ³ / ₄	660 x 935 x 660 26 x 36 ⁷ / ₈ x 26	660 x 1566 x 660 26 x 61 ³ / ₈ x 26	660 x 2002 x 628 26 x 78 ⁷ / ₈ x 24 ³ / ₄
Net Weight (kg/lb)	26/57	42/92	56.5/125	68/150
Gross Weight (kg/lb)	28/62	46/101	62/137	79.5/175

	C20G	C50G	C101G	C125G
Size (width - bottles)	30 cm - 20	60 cm - 54	60 cm - 100	60 cm - 125
Total Gross/Storing Volume (l)	62/57	152/134	315/286	390/350