

ILGLSE27NC017



This 13.5W retro-fit Integral LED Classic Globe (GLS) (large screw base) delivers a warm light and brightness. With a 1521 lumen output, this lamp is one of only a few true 100W filament bulb replacements available today. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for rooms with a single pendant fitting, living rooms, hallways and kitchens.

### Details

**Barcode:** 5055788208037

**Category:** Lamps

**Range Name:** Everyday

**Product Type:** GLS

**Warranty (Years):** 2

**CE RoHS:** Yes

### Physical Data

**Product Length (mm):** 122

**Product Width (mm):** 60

**Product Weight (g):** 185

**Material:** Plastic, Polycarbonate, Nickel plated brass

**Base Term:** Edison screw

**Bulb Base:** E27

**Construction:** Aluminium heat-sink, Injection moulded diffuser

**Globe Finish:** Frosted

**Globe Type:** Classic Globe (GLS)

**Bulb or Luminaire Shape:** Round

**Placement / Application:** Indoor, General Lighting

### Electrical Data

**Power (W):** 15.5

**Power Consumption (w):** 15.5

**Power Factor:** 0.5

**Wattage equivalent (W):** 100

**Amperage (mA):** 118

**Dimming:** Non-Dimmable

**Driver IC Manufacturer:** Silergy

**Driver Included:** Yes

**Electric Current:** AC  
**True Wattage Eq (W):** 100  
**EN:** EN-62560  
**LVD Certified:** Yes

## Light Data

**Luminous Flux in Lumens (lm):** 1521  
**Luminous efficacy (lm/W):** 98  
**Lumens Range:** 1500 to 2000  
**Correlated Colour Temperature (CCT) (K):** 2700  
**Colour Temperature Name:** Warm  
**Beam Angle:** 200  
**Colour Rendering Index (CRI):** 80  
**Frequency Range (Hz):** 50  
**Instant on (Less than 1 second):** Yes  
**LED Type:** Surface mounted device (SMD)  
**Lifetime (hours):** 15000  
**Switching Cycles:** 7500

## Environment

**EN:** EN-62560  
**LVD Certified:** Yes  
**CE RoHS:** Yes  
**Energy Rating:** A++  
**Hg 0% (Mercury Free):** Yes  
**IP Rating (Ingress Protection):** IP20  
**Lowest Operating Temperature (°C):** -20  
**Maximum Operating Temperature (°C):** 40

## Packaging

**Package Weight (g):** 223  
**Package Length (mm):** 135  
**Package Width (mm):** 68  
**Package Depth (mm):** 68  
**Qty per euro pallet:** 1050