

The SNR indicates the level of noise reduction provided

	Tested attenuation SNR	H	M	L
○ Engage	20 dB	21 dB	18 dB	16 dB
◐ Experience	23 dB	23 dB	20 dB	20 dB
● Quiet	26 dB	29 dB	23 dB	21 dB

Ear tip size: XS = 8mm, S = 10mm, M = 11mm, L = 12mm.

Noise Reduction Rating

14 / 17 / 20

ENGAGE / EXPERIENCE / QUIET

DECIBELS

(WHEN USED AS DIRECTED)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30 (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS)

LOOP BV
2600, BERCHEM, BELGIUM

LOOP SWITCH™ 2

FEDERAL LAW PROHIBITS REMOVAL OF THIS LABEL PRIOR TO PURCHASE



LABEL REQUIRED BY U.S. EPA REGULATION 40 CFR PART 211 SUBPART B

Tested according to EN 352-2:2020 and yearly control by PZT GmbH Bismarckstr. 264B, D26389 - Wilhelmshaven [NB 1974].

Designed in Belgium and manufactured in China.
Read instructions before use.

Loop BV, Posthofbrug 6/8, Bus 5/148, BE-2600, Berchem.

CE 1974 | EN 352 |

0-3

WARNING:

CHOKING HAZARD

