

STATUS

• ON
• AUTO
• STAND-BY

B&W Bowers & Wilkins

ASW608

Serial No. 0801-0012443



VOLUME (LINE)
MIN MAX

VOLUME (SPEAKER)
MIN 50 MAX
40 80

LOW-PASS FREQ
30 120 25 140

• IN
• OUT LOW-PASS FILTER

• A
• B
• C BASS EXTENSION

• A
• B EQ

• 0
• 180 PHASE

12V TRIGGER

LINE IN
R L

SPEAKER LEVEL IN
+ R - L +

CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN
AVIS: RISQUE DE CHOC ELECTRIQUE - NE PAS OUVRIR

COMPLIES WITH PART 15 OF THE FCC RULES
OPERATION IS SUBJECT TO THE FOLLOWING CONDITIONS:
1. THIS DEVICE DOES NOT CAUSE HARMFUL INTERFERENCE AND
2. THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED,
INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE
OPERATION

POWER
100-240V~ 50/60Hz 40W

T 4.0AH 250V

B&W Group Ltd. Worthing, UK
Designed in UK - Assembled in China - Assemblé en Chine

