

## DS-3E0505HP-E

### 5-Port Gigabit Unmanaged Hi-PoE Switch

DS-3E0505HP-E switches are layer 2 Hi-PoE switches, providing advanced PoE power supply technology and Gigabit networks design on the basis of high-performance access to ensure stable data upload. The switches support Hi-PoE, long range, port isolation, and PoE watchdog function.



#### Key Feature

- 3 × gigabit PoE ports, 1 × gigabit Hi-PoE port and 1 × gigabit RJ45 port.
- IEEE 802.3at/af/bt standard for Hi-PoE port (Max. 60 W PoE output).
- IEEE 802.3at/af standard for PoE ports (Max. 30 W PoE output).
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab standard.
- 6 KV surge protection for PoE ports.
- Up to 300 m long-range transmission.
- PoE watchdog to auto detect and restart the cameras that do not respond.
- Port isolation to improve network security.
- Gigabit network access design.
- Wire-speed forwarding.
- Store-and-forward switching.
- Solid high-strength metal shell.
- Reliable fan-free design.




## Specification


Model		DS-3E0505HP-E
Network parameters	Port number	3 × gigabit PoE ports, 1 × gigabit Hi-PoE port and 1 × gigabit RJ45 port
	Port type	RJ45 port, full duplex, MDI/MDI-X adaptive
	Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, and IEEE 802.3ab
	Forwarding mode	Store-and-forward switching
	Working mode	Standard mode (default), Extend mode, Isolation mode, PoE watchdog mode
	Ports for long-distance transmission	Ports 3 and 4
	MAC address table	2 K
	Switching capacity	10 Gbps
	Packet forwarding rate	7.44 Mpps
	Internal cache	1 Mbits
PoE power supply	PoE standard	Port 1: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt Ports 2 to 4: IEEE 802.3af, IEEE 802.3at
	PoE power pin	Ports 1 to 4: Ethernet cables 1/2/3/6 and 4/5/7/8 provide power supply simultaneously.
	PoE port	Ports 1 to 4
	Hi-PoE port	Port 1
	Max. port power	Port 1: 60 W Ports 2 to 4: 30 W
	PoE power budget	60 W
Dialing function	Long range	Ports 3 and 4: up to 300 m; and the speed rate of the port is 10 Mbps.
	Port isolation	Ports 1 to 4: port isolation mode to improve network security.
	PoE watchdog	Ports 1 to 4: auto detect and restart the cameras that do not respond.
General	Shell	Metal material, fan-free design
	Net Weight	0.27 kg (0.59 lb)
	Dimension (L × H × D)	121 mm × 88.1 mm × 27.6 mm (4.76" × 3.47" × 1.09")
	Operating temperature	-10 °C to 40 °C (14 °F to 104 °F)
	Storage temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating humidity	5% to 95% (no condensation)
	Storage humidity	5% to 95% (no condensation)
	Power supply	48 VDC, 1.35 A
	Power consumption in idle	< 5W
	Max. power consumption	65 W
Power source	65 W	
Approval	EMC	FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016)
	Safety	UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)
	Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)

## Physical Interface

Front panel:




Back panel:




## Available Model

DS-3E0505HP-E


Dimension (unit: mm)



## Typical Application



Distributed by



# HIKVISION

### Headquarters

No.555 Dianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5000  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-800-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-6233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-29499800  
sales@poms.hikvision.com

**Hikvision Canada**  
T +1-888-200-8000  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9948  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5642770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6802  
info.it@hikvision.com

**Hikvision Brazil**  
T +55-11-3218-2050  
Latin.Support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +603-7852-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +41628-902145  
sales.uk@hikvision.com

**Hikvision South Africa**  
T +27(10) 0561172  
sales.africa@hikvision.com

**Hikvision France**  
T +3301-86-330-160  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9230667  
nikita.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-374270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-9432080  
sales.me@hikvision.com

**Hikvision Singapore**  
T +65-6684-0710  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-757-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-67-1038-0438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-809-67-99  
sales.ru@hikvision.com

**Hikvision Korea**  
T +82-1031-732-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-60  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933769  
Sales.indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com