

Tested according to



<p>CE 2777 CAT III</p> <p>EN ISO 374-1:2016 +A1:2018/Type B EN ISO 374-5:2016</p> <p>KLOPT VIRUS</p>	<p>Chemical Permeation (EN ISO 374-1:2016+A1:2018/Type B)</p> <table border="1"> <thead> <tr> <th>Level</th> <th>EN ISO 374-4:2019 Degradation %</th> </tr> </thead> <tbody> <tr> <td>6</td> <td>-7,1 %</td> </tr> <tr> <td>1</td> <td>100 %</td> </tr> <tr> <td>6</td> <td>27 %</td> </tr> <tr> <td>4</td> <td>27,1 %</td> </tr> <tr> <td>5</td> <td>17,7 %</td> </tr> </tbody> </table> <p><i>Remark: Breakthrough times based upon laboratory test may not reflect the actual times due to external factors.</i></p>	Level	EN ISO 374-4:2019 Degradation %	6	-7,1 %	1	100 %	6	27 %	4	27,1 %	5	17,7 %	<p>EU Declaration of Conformity is accessible at www.ox-on.com/docs</p> <p>User information sheet is enclosed with this package.</p> <p>EN ISO 21420:2020</p>	
	Level	EN ISO 374-4:2019 Degradation %													
6	-7,1 %														
1	100 %														
6	27 %														
4	27,1 %														
5	17,7 %														
<p>EU Type Examination and On-Going Conformity, carried out by Notified Body 2777</p> <p>SATRA TECHNOLOGY EUROPE LTD BRACETOWN BUSINESS PARK CLONEE, DUBLIN D15 YKZP, IRELAND</p> <p>Components used in glove manufacturing may cause allergic reactions in some users. If allergic reactions occur, seek for medical advice immediately. Before usage, inspect the gloves for any defect or imperfections. Never use a damaged product.</p> <p>EN ISO 374-5:2016, clause 7 The penetration resistance has been assessed under laboratory conditions and relates only to the tested specimens. Protection against bacteria and fungi - Pass Protection against viruses - Pass</p> <table border="1"> <thead> <tr> <th>Breakthrough Time (BTT)</th> <th>Performance Level</th> </tr> </thead> <tbody> <tr> <td>BTT > 10 min.</td> <td>Level 1</td> </tr> <tr> <td>BTT > 30 min.</td> <td>Level 2</td> </tr> <tr> <td>BTT > 60 min.</td> <td>Level 3</td> </tr> <tr> <td>BTT > 120 min.</td> <td>Level 4</td> </tr> <tr> <td>BTT > 240 min.</td> <td>Level 5</td> </tr> <tr> <td>BTT > 480 min.</td> <td>Level 6</td> </tr> </tbody> </table>	Breakthrough Time (BTT)	Performance Level	BTT > 10 min.	Level 1	BTT > 30 min.	Level 2	BTT > 60 min.	Level 3	BTT > 120 min.	Level 4	BTT > 240 min.	Level 5	BTT > 480 min.	Level 6	<p>This product complies with PPE Regulation EU 2016/425 for special purpose.</p>
Breakthrough Time (BTT)	Performance Level														
BTT > 10 min.	Level 1														
BTT > 30 min.	Level 2														
BTT > 60 min.	Level 3														
BTT > 120 min.	Level 4														
BTT > 240 min.	Level 5														
BTT > 480 min.	Level 6														

LOT 210736

02-2023

01-2028

OX-ON A/S · Kometvej 36 · 6230 Roedekro · Denmark · www.ox-on.com

Art. No.: 93939

DB No.: 2341182



GLOVE SIZE



Made in China