### MR11 GU10 BULB 330LM 3.2W 2700K DIMMABLE 36 BEAM 80 CRI INTEGRAL

ILMR11DC011



This MR11 GU10 lamp provides the light output of a 40W halogen lamp for only 3.6W. This spotlight offers excellent dimming performance when installed with compatible dimmer switches, giving precise control of your environment. Ideal for residential or commercial interiors.

### **Details**

Quick Order Code: Barcode: Category: Range Name: Product Type:	748239 5055788237129 Lamps 240V GU10 Base MR11 GU10
Product Body Finish:	Matt white
Market Segment: Warranty (Years):	Commercial indoor, Residential indoor 2
CE RoHS:	Yes
Physical Data	
Product Length (mm):	48
Product Width (mm):	35
Product Weight (g):	35
Material:	Plastic
Base Term:	GU10
Bulb Base:	GU10
Construction:	Plastic heat-sink, Injection moulded diffuser
Bulb Fixing:	Downlight
Bulb or Luminaire Shape:	Round
Placement / Application:	Indoor, General Lighting

#### **Electrical Data**

Power (W):	3.2
Power Consumption (w):	3.2
Power Factor:	0.4
Wattage equivalent (W):	40
Amperage (mA):	22


Dimming:	Dimmable
Driver Included:	Yes
Electric Current:	AC
True Wattage Eq (W):	40
EN:	EN-62560
LVD Certified:	Yes

# Light Data

Luminous Flux in Lumens (Im):	290
Luminous efficacy (Im/W):	103
Peak Intensity (Cd):	600
Correlated Colour Temperature (CCT) (K):	2700
Colour Temperature:	2700K - Warm
Colour Temperature Name:	Warm
Beam Angle:	36
Colour Rendering Index (CRI):	80
Compatible Dimmers:	Varilight
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	15000
Switching Cycles:	7500
Useful Lumens (Im):	300

### Environment

EN:	EN-62560
LVD Certified:	Yes
CE RoHS:	Yes
Energy Rating:	A+
New Energy Rating:	E
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40



Portal.integral-led.com

## Packaging

Package Weight (g):	42
Package Length (mm):	40
Package Width (mm):	40
Package Depth (mm):	60

### Portal.integral-led.com