

## Ultra-compact, high performance charger for worldwide charging

Available in:

20 A  
12 V

40 A  
12 V


60 A  
12 V



TRUECharge2 battery chargers lead the industry with a small footprint and ultra-compact design. In addition to meeting global safety and regulatory standards, TRUECharge2 battery chargers feature low electrical interference and efficient, power factor corrected multistage charging. Thanks to their inherent drip-proof design characteristics, the TRUECharge2 chargers can be mounted in multiple positions. Designed for recreational and commercial applications worldwide, TRUECharge2 accepts 90 - 265 Vac, 47-63 Hz which makes traveling abroad and handling poor-quality power a breeze. The easy-to-read display of the TRUECharge2 20 A, 40 A and 60 A 12 V models can be augmented with an optional remote panel. Each models comes with built-in protection against surges and spikes on the AC power line.

### Performance Features

- » TRUECharge2 20 A, 40 A and 60 A are equipped with PARALLEL STACKING feature. This allows two chargers to work together to combine the output current, achieving up to 120 A for large battery banks. This requires the optional Remote Panel (part #808-8040-01)
- » Microprocessor-controlled, multistage charging algorithms
- » Settings for two and three-stage charging
- » Settings for flooded, gel, AGM or lead-calcium batteries
- » Battery-equalization feature
- » Ability to charge batteries drained to extremely low voltage
- » Optional battery temperature sensor (Part #808-0232-01)



### Protection Features

- » Reverse battery polarity protection
- » Drip-proof design
- » Over and under-temperature protection
- » DC over-voltage protection

### Three-Stage Charging

Multistage charging ensures batteries receive optimum charging, but with minimal wear and tear, regulating the voltage and current delivered to the batteries in three automatic stages:

- » Bulk: Replaces 70-80% of the battery's state-of-charge at the fastest possible rate
- » Absorption: Replenishes the remaining 20-30% of charge, bringing the battery to a full charge at a slow, safe rate
- » Float: Voltage is reduced and held constant in order to prevent damage and maintain batteries at a full charge

### Power Factor Corrected (PFC) Charging

Less shorepower is required for charging batteries, freeing up more usable AC power for running electrical devices and appliances and reducing the likelihood of tripping shorepower breakers

### Applications:



Recreational vehicles



Marine



Heavy duty trucks



Work vehicles



Buses / coaches



Specialty vehicles



UL 1564, UL 1236  
Including Marine Supplement



### Xantrex LLC

3700 Gilmore Way  
Burnaby, British Columbia  
Canada V5A 4B5  
800 670 0707 Toll Free  
604 420 1591 Fax

541 Roske Drive, Suite A  
Elkhart, Indiana  
USA 46516  
800 446 6180 Toll Free  
574 294 5989 Fax

[www.xantrex.com](http://www.xantrex.com)

Electrical specifications (@ 25°C unless otherwise noted)	TRUECHARGE2 20 / 40 / 60
Output current (nominal)	20 A / 40 A / 60 A
Output voltage (nominal, depending on settings)	
Charge	14.2 - 15.5 Vdc
Float	13.4 - 13.8 Vdc
Equalize	16 Vdc
DC output connections	Three
AC input voltage*	90-265 Vac 47-63 Hz 120 Vac, 230 Vac, 240 Vac nominal
Temperature compensation	Three settings
Charger efficiency	> 80%
Battery type	Gel, Flooded, AGM, Pb-Ca
Minimum recommended battery bank size	40 Ah / 80 Ah / 120 Ah

General specifications	
Operating temperature**	0 to 60°C (32 - 140°F)
Storage temperature	-40 to 80°C (-40 - 176°F)
Battery connection	Three positive terminals One negative terminal
Dimensions (H x W x L)	<b>20 A &amp; 40 A</b> - 2.8 x 6.7 x 9.8" (70 x 170 x 250mm) <b>60 A</b> - 3.5 x 6.7 x 13.4" (90 x 170 x 340 mm)
Weight	<b>20 A &amp; 40 A</b> - 4.8 lb (2.2 kg) <b>60 A</b> - 9.9 lb (4.5 kg)
Warranty	Two year
Part Numbers	804-1220-02 / 804-1240-02 / 804-1260-02

Accessories	
Remote panel	808-8040-01
Battery temperature sensor	808-0232-01

**Regulatory and environmental compliance**

RCM, CSA E60335-2-29, UL1564, and UL1236 including the Marine Supplement, drip test, and Ignition Protection ratings. CE Marked for the Low Voltage Directive (safety) and the EMC Directive. Complies with IEC 60335-2-29 including Australian deviations. Ingress protection rating IP32 per EN/IEC 60529. Complies with FCC Part 15B and Industry Canada ICES-003 Class B emissions limits. Complies with ABYC A-31

Note: Specifications subject to change without notice. \*90 - 104 Vac ± 4 Vac output de-rated to 80% of full load current. \*\*Output current derates above 50°C (except 40A model which derates above 40°C). Highly Accelerated Life Tested (HALT) to -20°C.