

Comparison Melitta® CAFFEO® Fully Automatic Machines

Overview of features

Each Melitta® CAFFEO® model range has its own unique features. The table below helps you to get a quick overview.



Technical characteristics

	CAFFEO Barista® TSP	CAFFEO Barista® TS	CAFFEO Barista® T	CAFFEO® Varianza® CSP	CAFFEO® Varianza® CS
Adjustable brewing temperature	3 positions	3 positions	3 positions	3 positions	3 positions
Continuously adjustable flow regulator for coffee	30–220 ml	30–220 ml	30–220 ml	25–220 ml	25–220 ml
Pre-brewing function	•	•	•	•	•
Integrated hot water outlet	•	•	•	•	•
Coffee outlet for 1 or 2 cups	•	•	•	•	•
All-in-one outlet for 2 coffee/milk specialties at the same time	•	•	•	—	—
Height-adjustable coffee outlet	140 mm	140 mm	140 mm	135 mm	135 mm
Premium steel grinder	•	•	•	•	•
Grinding fineness	5 positions	5 positions	5 positions	5 positions	5 positions
Ground coffee chute	•	•	•	—	—
Automatic regulation of ground coffee quantity	•	•	•	•	•
2-chamber bean container	automatically	automatically	manually	—	—
My Bean Select	—	—	—	•	•
Best Aroma System	• (Plus)	• (Plus)	•	• (Plus)	• (Plus)
Capacity of bean container	270 g (2 x 135 g)	270 g (2 x 135 g)	270 g (2 x 135 g)	125 g	125 g
Bean container with Aromasafe®	•	•	•	•	•
Active monitored filling level bean container	•	•	—	—	—
Programmable coffee strength	5 positions	5 positions	5 positions	5 positions	5 positions
Noise reduction	•	•	•	•	•
Milk froth system	One-Touch Venturi-System	One-Touch Venturi-System	One-Touch Venturi-System	One-Touch Venturi-System	Auto Cappuccinatore
External milk container	Thermo	•	model depending	•	—
Sensor control panel	•	•	•	—	—
Rotary Switch	—	—	—	—	—
LED cup illumination	•	•	—	•	—
Display	TFT colour display	TFT colour display	TFT colour display	TFT colour display	LED symbol display
Programmable dispensing button	•	•	•	•	•
My coffee function	• (8 profiles)	• (4 profiles)	• (4 profiles)	—	—
Number of default coffee variations	21	18	18	10	3
Original preparation process for cappuccino	•	•	•	•	—
Stainless steel drip tray	•	•	•	•	•
Cup warming plate (passive)	• (Stainless steel)	•	•	•	•
Automatic cleaning and descaling programme	•	•	•	•	•
Simplest hygiene by Easy Steam Cleaning (Milk)	•	•	•	•	—
Removable brewing unit	•	•	•	•	•
Capacity of water container	1,8 l	1,8 l	1,8 l	1,2 l	1,2 l
Presetting of water hardness (4 positions)	•	•	•	•	•
Compatible with Claris® waterfilter	•	•	•	•	•
Automatic indication for changing water filter	•	•	•	•	•
Auto OFF function	•	•	•	•	•
0 watt button	•	•	•	•	•
Energy-saving-mode (50% less current consumption)	•	•	•	•	•
Pump pressure	15 bar	15 bar	15 bar	15 bar	15 bar
Length of cable	1 m	1 m	1 m	1 m	1 m
Cable rewind facility	•	•	•	—	—
Rolls in the back area	•	•	•	—	—
Available colours	black, Stainless steel	silver, black, Stainless steel	silver, black, Stainless steel	silver, black, Stainless steel	black
Wattage	max. 1450 W	max. 1450 W	max. 1450 W	max. 1450 W	max. 1450 W
Voltage	220–240 V	220–240 V	220–240 V	220–240 V	220–240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Weight of device	ca. 10,7 kg	ca. 10,4 kg	ca. 10,3 kg	ca. 8,8 kg	ca. 8,2 kg
Dimensions: (Height x Width x Depth in mm)	372 x 259 x 467	372 x 259 x 467	372 x 259 x 467	405 x 253 x 380	405 x 253 x 380

Comparison Melitta® CAFFEO® Fully Automatic Machines

Overview of features

Each Melitta® CAFFEO® model range has its own unique features. The table below helps you to get a quick overview.



Technical characteristics	CAFFEO® CI®	CAFFEO® Passione®	CAFFEO® Gourmet	CAFFEO® BISTRO
Adjustable brewing temperature	3 positions	3 positions	3 positions	3 positions
Continuously adjustable flow regulator for coffee	30–220 ml	25–220 ml	30–220 ml	30–220 ml
Pre-brewing function	•	•	•	•
Integrated hot water outlet	•	•	•	•
Coffee outlet for 1 or 2 cups	•	•	•	•
All-in-one outlet for 2 coffee/milk specialties at the same time	•	—	—	—
Height-adjustable coffee outlet	140 mm	135 mm	130 mm	135 mm
Premium steel grinder	•	•	•	•
Grinding fineness	3 positions	5 positions	3 positions	3 positions
Ground coffee chute	•	—	•	•
Automatic regulation of ground coffee quantity	•	•	•	•
2-chamber bean container	manually	—	manually	manually
My Bean Select	—	—	—	—
Best Aroma System	—	•	—	—
Capacity of bean container	270 g (2 x 135 g)	125 g	270 g (2 x 135 g)	270 g (2 x 135 g)
Bean container with Aromasafe®	•	•	•	—
Active monitored filling level bean container	—	—	—	—
Programmable coffee strength	4 positions	5 positions	5 positions	4 positions
Noise reduction	•	•	•	—
Milk froth system	One-Touch Venturi-System	Auto Cappuccinatore	Perfect Cappuccino steam nozzle	Perfect Cappuccino steam nozzle
External milk container	model depending	—	—	—
Sensor control panel	—	—	—	—
Rotary Switch	•	—	•	—
LED cup illumination	•	—	—	—
Display	LCD textdisplay	LED symboldisplay	LCD textdisplay	LED symboldisplay
Programmable dispensing button	•	•	•	—
My coffee function	• (4 profiles)	—	—	—
Number of default coffee variations	4	3	2	2
Original preparation process for cappuccino	•	—	—	—
Stainless steel drip tray	•	•	•	•
Cup warming plate (passive)	• (Stainless steel)	•	•	•
Automatic cleaning and descaling programme	•	•	•	•
Simplest hygiene by Easy Steam Cleaning (Milk)	•	•	—	—
Removable brewing unit	•	•	•	•
Capacity of water container	1,8 l	1,2 l	1,8 l	1,8 l
Presetting of water hardness (4 positions)	•	•	•	•
Compatible with Claris® waterfilter	•	•	•	•
Automatic indication for changing water filter	•	•	•	—
Auto OFF function	•	•	•	Stand-by-function
0 watt button	•	•	•	power switch
Energy-saving-mode (50% less current consumption)	•	•	•	•
Pump pressure	15 bar	15 bar	15 bar	15 bar
Length of cable	1 m	1 m	1 m	1 m
Cable rewind facility	•	—	•	•
Rolls in the back area	•	—	•	—
Available colours	silver, black, white, anthracite	silver, black, Stainless steel	silver, black	silver, black
Wattage	max. 1400 W	max. 1450 W	max. 1500 W	max. 1500 W
Voltage	220–240 V	220–240 V	220–240 V	220–240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Weight of device	ca. 9,6 kg	ca. 8,0 kg	ca. 9,0 kg	ca. 8,4 kg
Dimensions: (Height x Width x Depth in mm)	352 x 255 x 473	390 x 253 x 380	354 x 274 x 475	354 x 274 x 475


Comparison Melitta® CAFFEO® Fully Automatic Machines

Overview of features

Each Melitta® CAFFEO® model range has its own unique features. The table below helps you to get a quick overview.



CAFFEO®
SOLO®&
perfect milk



CAFFEO®
SOLO®& milk



CAFFEO®
SOLO®

Technical characteristics

Technical characteristics	CAFFEO® SOLO®& perfect milk	CAFFEO® SOLO®& milk	CAFFEO® SOLO®
Adjustable brewing temperature	3 positions	3 positions	3 positions
Continuously adjustable flow regulator for coffee	30–220 ml	30–220 ml	30–220 ml
Pre-brewing function	•	•	•
Integrated hot water outlet	•	•	—
Coffee outlet for 1 or 2 cups	•	•	•
All-in-one outlet for 2 coffee/milk specialties at the same time	—	—	—
Height-adjustable coffee outlet	135 mm	135 mm	135 mm
Premium steel grinder	•	•	•
Grinding fineness	3 positions	3 positions	3 positions
Ground coffee chute	—	—	—
Automatic regulation of ground coffee quantity	•	•	•
2-chamber bean container	—	—	—
My Bean Select	—	—	—
Best Aroma System	—	—	—
Capacity of bean container	125 g	125 g	125 g
Bean container with Aromasafe®	—	—	—
Active monitored filling level bean container	—	—	—
Programmable coffee strength	3 positions	3 positions	3 positions
Noise reduction	model depending	—	model depending
Milk froth system	Auto Cappuccinatore	Panarello	—
External milk container	—	—	—
Sensor control panel	—	—	—
Rotary Switch	—	—	—
LED cup illumination	—	—	—
Display	LED symboldisplay	LED symboldisplay	LED symboldisplay
Programmable dispensing button	—	—	—
My coffee function	—	—	—
Number of default coffee variations	2	2	2
Original preparation process for cappuccino	—	—	—
Stainless steel drip tray	•	•	•
Cup warming plate (passive)	•	•	•
Automatic cleaning and descaling programme	•	•	•
Simplest hygiene by Easy Steam Cleaning (Milk)	—	—	—
Removable brewing unit	•	•	•
Capacity of water container	1,2 l	1,2 l	1,2 l
Presetting of water hardness (4 positions)	•	•	•
Compatible with Claris® waterfilter	•	•	•
Automatic indication for changing water filter	•	•	•
Auto OFF function	•	•	•
0 watt button	•	•	•
Energy-saving-mode (50% less current consumption)	•	•	•
Pump pressure	15 bar	15 bar	15 bar
Length of cable	1 m	1 m	1 m
Cable rewind facility	•	•	•
Rolls in the back area	—	—	—
Available colours	silver/black, black, Special Edition	silver/black	silver/black, black, Special Edition
Wattage	max. 1400 W	max. 1400 W	max. 1400 W
Voltage	220–240 V	220–240 V	220–240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Weight of device	ca. 8,1 kg	ca. 8,1 kg	ca. 8,0 kg
Dimensions: (Height x Width x Depth in mm)	325 x 200 x 455	325 x 200 x 455	325 x 200 x 455