



- B** Gross bar 12 using the middle straight connection, force screw in place.
- C** The top of the rod 12 parts using G direct connection, the connection after the pole changed to 6
- D** Top six claw 1
- E** With three links, 6
- F** 3 links 6
- G** Straight through 6

Method:

Step 1: The bottom of the tent is paved, and the tent is rolled into the tent at the bottom edge, followed by F connection.

Step 2: The tent is rolled into the tent inside, and then the tent is connected to the B pipe.



Attention: Please do not use the tent in the rain. The tent is not suitable for use in the rain. Please do not use the tent in the rain. Please do not use the tent in the rain.

000006104

5 902802 907163

MADE IN P.R.C.

SHENZHEN HONGYUAN TENT CO., LTD.
 HONGYUAN TENT CO., LTD.
 NO. 1000, HONGYUAN TENT CO., LTD.
 HONGYUAN TENT CO., LTD.
 HONGYUAN TENT CO., LTD.

SHENZHEN HONGYUAN TENT CO., LTD.
 HONGYUAN TENT CO., LTD.
 NO. 1000, HONGYUAN TENT CO., LTD.
 HONGYUAN TENT CO., LTD.
 HONGYUAN TENT CO., LTD.

M: 528

CE

EN

MADE IN CHINA