

- Toner Frequency: High alternating
- Low alternating 446-657 Hz
- Talk Battery: 9V into a 600 ohms circuit
- Voltage protection: 50 VDC or 24 VAC
- Battery: 9V DC standard or alkaline
- CE Approved: EN 55022 Class B for ITE and EN 55024
- Size: 125 (L) x 68 (W) x 26 (H) mm (4.9 x 2.7 x 1.2 in.)
- Weight: 120g (.37 lb)

Net Probe

- Gain: 30 db
- Tip resistance: 30 ohms (Plastic tip)



IC Intracom Vertriebs GmbH
Löhbacher Str.7
58553 Halver | Germany

Made in Taiwan
Rev 5.02
515566

Intellinet Network Solutions® offers a complete line of active and passive networking products. Ask your local computer dealer for more information or visit us online at

intellinet-network.com

© IC Intracom. All rights reserved.

All trademarks and trade names are those of their respective owners.

Warning: This product contains chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

- Size: 210 (L) x 40 (W) x 28 (H) mm (8.1 x 1.6 x 1.1 in.)
- Weight: 140g (.30 lb)

Environmental:

- Operating temperature: 0 – 40°C (32 – 104°F)

Package Contents

- Net Probe
- Net Toner w/ Alligator clips and RJ-12 connector
- Female F-connector to RJ-45 adapter
- Carrying pouch
- User Manual

