



# AIRONEX

## LUCHTONTVOCHTIGER



**WARNING**

The appliance is equipped with flammable gas R290. Before using the appliance, please read the manual. Before installing the appliance, please read the installation manual. If inside housing, contact the nearest authorized Service Centre and strictly follow manufacturer's instructions only.

**WARNING:**  
Appliance shall be installed, operated and stored in a room with a floor area larger than 4m<sup>2</sup>.  
Do not use other ways to accelerate the defrosting process or clean other than the ways recommended by manufacturer.  
The appliance shall be stored in a room without continuously operating ignition sources (for example, naked fire, an operating gas appliance or an operating electric heater).  
Do not pierce or touch.  
Please notice whether refrigerant contains colour or not.

Warning: flammable materials

**DEHUMIDIFIER**  
Model: L012

**CE**

Dehumidification Capacity	45L/D (37°C/60%) 12L/D (27°C/60%) 6L/D (19°C)
Rated Voltage	230V
Rated Frequency	50Hz
Rated Input Power	115W (37°C/60%)
Max Rated Input Power	115W (37°C/60%)
Max Rated Input Current	0.5A (37°C/60%)
Rated Tank Capacity	2L
Sound Power Level	3.8dB(A)
Refrigerant Charge	R290 (5g)
Net Weight	10kg
Max. Input Voltage/Current	250V/10A (250V)
Max. Input Power	2500W
Max. Input Current	10A
Max. Input Voltage	250V
Max. Input Power	2500W
Max. Input Current	10A
Max. Input Voltage	250V

First emergency repairman  
after-sales service  
Production year:  
2020/10

**NOTE:**  
Appliance shall be installed, operated and stored in a room with a floor area larger than 4m<sup>2</sup>.

Warning: flammable materials

### SPECIFICATIES:

**SPANNING:** AC220-240V

**FREQUENTIE:** 50HZ

**GESCHAT STROOMVERBURIK:** 1,2A

**KOUDEMIDDEL/HOEVEELHEID:** R290/50



Sanco Air-Technology BV  
Wolkeek Pijnmontstraat 13  
5652 AD Eindhoven  
Made in PRC

