54V CHAINSAW DCMCS574, DCMCS575

Congratulations!

You have chosen a DEWALT tool. Years of experience, thorough product development and innovation make DEWALT one of the most reliable partners for professional power tool users.

Technical Data

		DCMCS574	DCMCS575
oltage	Vac	54	54
Туре		1	1
Battery type		Li-lan	Li-lon
Bar Length	cm	45	50
Maximum Chain Speed (no-load)	m/s	15	15
Maximum Cutting Length	cm	40	45
Oil Capacity	ml	115	115
Weight (without battery pack)	kg	5	5.7

Noise values and/or vibration values (triax vector sum) according to EN60745-2-13:2009+A1:2010:

LM	(emission sound pressure level)	dB(A)	83	83
Lw	(sound power level)	dB(A)	99	100
K	(uncertainty for the given sound level)	dB(A)	1,8	2
Vi	bration emission value a _h =	m/s²	4.4	4.1
Uncertainty K =		m/s²	1.5	1.5

The vibration and/or noise emission level given in this information sheet has been measured in accordance with a standardised test given in EN60745 and may be used to compare one tool with another. It may be used for a preliminary assessment of exposure.



WARNING: The declared vibration and/or noise emission level represents the main applications of the tool. However if the tool is used for different applications, with different accessories or poorly maintained, the vibration and/or noise emission may differ. This may significantly increase the exposure level over the total working period.

An estimation of the level of exposure to vibration and/ or noise should also take into account the times when the tool is switched off or when it is running but not actually doing the job. This may significantly reduce the exposure level over the total working period.

Identify additional safety measures to protect the operator from the effects of vibration and/or noise such as: maintain the tool and the accessories, keep the hands warm (relevant for vibration), organisation of work patterns.

EC-Declaration of Conformity

Machinery Directive



54V Chainsaw DCMCS574, DCMCS575

DEWALT declares that these products described under Technical Data are in compliance with: 2006/42/EC, EN62841-1:2015, EN62841-4-1:2020.

2000/14/EC, Annex V

L_{wx} (measured sound power level) 99 dB(A) (DCMCS574)/100 dB(A)DCMCS575, Uncertainty (K)

1.8 dB(A) (DCMCS574)/2.0 dB(A)DCMCS575,

L_{ex} (guaranteed sound power) 102 dB(A)

These products also comply with Directive 2014/30/EU and 2011/65/EU. For more information, please contact DEWALT at the following address or refer to the back of the manual.

The undersigned is responsible for compilation of the technical file and makes this declaration on behalf of DEWALT.

Markus Rompel

Vice-President Engineering, PTE-Europe DEWALT, Richard-Klinger-Straße 11, 65510, Idstein, Germany 15.10.2021

THE SUPPLY OF MACHINERY (SAFETY) REGULATIONS 2008

54V Chainsaw DCMCS574, DCMCS575

DEWALT declares that these products described under "technical data" are in compliance with:

The Supply of Machinery (Safety) Regulations, 2008, S.I. 2008/1597 (as amended), EN62841-1:2015, EN62841-4-1:2020.

The Noise Emission in the Environment by Equipment for use Outdoors Regulations 2001, SJ. 2001/1701 (as amended), Schedule 8.

> L_{wA} (measured sound power level) 99 dB(A) (DCMCSS74)/100 dB(A)DCMCSS75,