# WIRELESS

# \* FEATURES

Device name: Wireless receiver

Call number: support Voice prompt: support

Chinese and English dual voice: support

(default English)
Drag two: support

Pairing timeout shutdown: pairing state

lasts 5 minutes atter shutdown

Low voltage reminder: when the voltage is less than 3.2V reminder, every 5 seconds to remind 1 times, 3.1V

shutdown

### \* Systern state

Power off: MFB long by 3 seconds
Volume pius: short press VOL+
Volume reduction: short press VOLToggle language: double click on the
pairing state (red and blue lights on fiash)
to hold down MFB

### \* Telephone control

short

Answer the phone: call by MFB
Refused to answer the phone calls: long
press MFB
No number redlal: double-click the MFB
button, then press MFB to cancel out



### \* LED light display

Boot pairing: red and blue lights flash

alternately

Connection status: blue light slow flash

(5 seconds 1)

Low voltage: red light flash (0.5 sec. 1)

### \* Music control

Play pause: press MFB

Last one: VOL- long press 2 seconds Next: VOL+ long press 2 seconds

## \* Operating current

State parameter (4.00V) parameter (3.40V)

Rated voltage 4.00V 3.40V

Paired state current 4.33mA-20.56mA

4.47mA-22.03mA

Standby current (connected Wireless)

0.43mA-8.31mA 0.41mA-8.74mA

Play music current 19.04mA-23.21mA.

22.85mA-23.74mA

Talk current 23.82mA-24.05mA

25.19mA-25.78mA

Charging current 100.0mA. 100.0mA

Shutdown current 1.4uA 1.1uA



MADE IN CHINA