

CE Maintenance

1. Use careful with the earphone maybe excessive sound pressure from earphones and headphones can cause hearing loss.
2. The product shall only be connected to a USB interface of version USB2.0.
3. Adapter shall be installed near the equipment and shall be easily accessible.
4. EUT Operating temperature range: 0°C-40°C .
5. Adapter:
The plug considered as disconnect device of adapter
Power supply and ADP (rating):
 - ① Input: AC 100-240 V 50/60 Hz 4.0 A
Output: DC 19.0 V 13.16 A
 - ② Input: AC 200-240 V 50 Hz 2.0 A
Output: DC 19.0 V 11.58 A
6. The device complies with RF specifications when the device is used at a distance of 20 cm away from your body.
7. To prevent possible damage to hearing, do not listen at high volume levels for long periods.



Declaration of Conformity

Chengdu XGIMI Technology Co., Ltd. hereby declares that this product is in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU.

This product is allowed to be used in some of EU member states. For example, the device can be used in the following Member States:

Operations in the 5.15-5.25 GHz band are restricted to indoor usage only.

This Frequency applies to the following Member States or the geographical area within a Member State where restrictions on putting into service or requirements for authorisation of use exist.



BE	HR	AT
BG	IT	PL
CZ	CY	PT
DK	LV	RO
DE	LT	SI
EE	LU	SK
IE	HU	FI
EL	MT	SE
ES	NL	UK
FR		

IC Warning

This device complies with Industry Canada licence-exempt RSS standard(s).

Operation is subject to the following two conditions:

- (1) This device may not cause interference, and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.