

STATUS

• ON  
• AUTO  
• STAND-BY

**B&W** Bowers & Wilkins

**ASW608**

Serial No. 0801-0012443



VOLUME (LINE)  
MIN MAX

VOLUME (SPEAKER)  
MIN 50 MAX  
40 80

LOW-PASS FREQ  
30 120 25 140

• IN  
• OUT LOW-PASS FILTER

• A  
• B  
• C BASS EXTENSION

• A  
• B EQ

• 0  
• 180 PHASE

12V TRIGGER

LINE IN  
R L

SPEAKER LEVEL IN  
+ R - L +

**CAUTION**  
RISK OF ELECTRIC SHOCK  
DO NOT OPEN  
AVIS: RISQUE DE CHOC ELECTRIQUE - NE PAS OUVRIR

COMPLIES WITH PART 15 OF THE FCC RULES  
OPERATION IS SUBJECT TO THE FOLLOWING CONDITIONS:  
1. THIS DEVICE DOES NOT CAUSE HARMFUL INTERFERENCE AND  
2. THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED,  
INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE  
OPERATION

POWER  
100-240V~ 50/60Hz 40W

T 4.0AH 250V

B&W Group Ltd. Worthing, UK  
Designed in UK - Assembled in China - Assemblé en Chine

