



## 2USB chargeUP

### General Information

Name	chargeUP 12W 2,4A
SKU	2U-449450

### Basics

Brand	2USB
Model Number	JP-3501BD
EAN	8718868449450
Customs Number (HS-Code)	8504.40.82.90
Color	Tele Grey

### Dimensions

Depth (mm)	33
Height (mm)	45
Width (mm)	52
Nett Weight (gram)	76
Gross Weight (gram)	108
Mounting Depth (mm)	32

### Technical Specifications

Rated Voltage	100 - 250V~ 50/60Hz
Input Current	Max.1,5A
Input terminals	Screw terminals
Input wiring	0,75 mm2 - 2x2,5mm2 rigid, rigid-stranded or flexible
Stripping Length (mm)	6
Output Ports	1 x USB-A
Output Voltage	4,75 - 5,25VDC
Output Current	0,01 - 2,4A
Energy Efficiency (%)	>85
Stand-by Power (mW)	<50
Expected lifetime in hours at Full Load	30.000
Overvoltage Category (OVC)	II
Operating Temperature	0-40°C
Storage Temperature	-20°C - 80°C

### Standards & Certifications

Certifications	CB
CE Compliant	✓
EU Directives	RoHS Directive (2011/65/EU), EMC Directive (2014/30/eu), Low Voltage Directive (2014/35/EU), ErP Directive (2009/125/EC)
EMC & LVD Standards	EN 55032 (class B), EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010, EN 55024-A1:2014, IEC-EN 60950-1