QuickSpecs

Overview

HP USB Business Slim Keyboard

Models

HP USB Business Slim Keyboard

N3R87AA

Introduction

Enjoy easy data entry and wireless connectivity with the HP USB Business Slim Keyboard, designed to complement the 2015 class of HP Business PCs.

Key Benefits

- Interact seamlessly with a full-sized keyboard layout that's optimized for use with multiple operating systems.
- Feel free to move around the desk or table with a keyboard that keeps working up to 30 ft (10 m) away from your PC through a2.4 GHz wireless connection.
- Avoid surprises with a convenient LED that alerts you when you need to change the batteries.
- Get the reassurance of a one-year limited warranty.

Compatibility

The HP USB Business Slim Keyboard is compatible with HP ProDesk 600 G2 MTW, HP ProDesk 600 G2 SFF, HP ProDesk 600 G2 Desktop Mini, HP ProOne 600 G2 AlO 21.5" Touch, HP ProOne 600 G2 AlO 21.5" Non-Touch, HP EliteDesk 705 G2 MT HP EliteDesk 705 G2 SFF, HP EliteOne 705 G2 AlO 23" Touch, HP EliteOne 705 G2 AlO 23" Non-Touch and HP EliteDesk 705 G2 Desktop Mini

Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.



QuickSpecs

Summary of changes

HP USB Business Slim Keyboard

Dimensions (H x L x W) 1.09 x 18.1 x 6.47 in (27.87 x 460.3 x 164.3 mm

Keyboard Weight – Without Two AA 1.94 lb (880 g)

Alkaline Batteries

Dimensions (H x L x W) 1.46 x 4.53 x 2.47 in (37 x 115 x 62.9 mm)

Mouse Weight – Without Two AA 0.15 lb (67 g)

Alkaline Batteries

Dimensions (H x L x W) 0.33x 1.79 x 0.72 in (8.4 x 45.5 x 18.4 mm)

Weight 0.21 oz (5.9 g)

Cable Length – Minimum 6 ft (1.8 m)

Range 32.8 ft (10 m)

System Requirements Available USB port for the receiver

CD-ROM Drive

Product Safety UL; CSA /TUV (Europe only); CE Mark; CB Report Ergonomics ANSI; ISO (Europe only); GS Mark (Germany only)

EMC FCC; CE; ACA (-tick); BSMI; KC; VCCI

CE Mark EN 55022:2010; EN 55024; EN 301489-1; EN 61000

Design Guidelines for PCs PC 99 - connector overmold colors; PC 2001 - full functionality

Telecom All local telecom requirements and approvals for intended

markets

Approvals USA FCC Title 47 CFR, Par 15, Subpart C; other local requirements

Country Support US, Belgium, Switzerland, Spain, Denmark, Netherlands, France,

Germany, Italy, Portugal, Sweden, Norway, Finland, UK, Poland, Czech Republic, Turkey, Greece, Austria, Bulgaria, Cyprus, Estonia, Hungary, Ireland, Latvia, Lithuania, Luxemburg, Malta, Romania, Slovakia, Slovenia, Vietnam, HK, Australia, NZ, Malaysia, Singapore, Indonesia, Philippines, Thailand, Canada, China, Japan, Korea, Taiwan, India, Venezuela, Ecuador, Russia, Ukraine, Israel, Croatia, United Arab Emirates, Peru, Brazil, Chile,

Argentina, Mexico, South Africa, and up to 193 countries

worldwide.

Environmental Keyboard contains 25% post-consumer recycled plastic material.

Encryption 128bit AES Encryption

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



¹ See product QuickSpecs for compatible operating systems.

QuickSpecs

Summary of changes

Date of change:	Version History:		Description of change:
9/1/2015	Version 1 to 2		Edit title on p2
9/18/2015	Version 2 to 3		Change product name to "HP USB Business Slim Keyboard"
11/30/2015	Version 3 to 4	Changed	Part number to N3R87AA

